

Aalborg Universitet

Glass as an active component of functional materials

An invited talk Yue, Yuanzheng

Publication date: 2014

Document Version Accepted author manuscript, peer reviewed version

Link to publication from Aalborg University

Citation for published version (APA):

Yue, Y. (2014). Glass as an active component of functional materials: An invited talk. Abstract from 7th Symposium on China Functional Glasses and International Forum on New Photoelectronic Materials, Hangzhou, China.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
 You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Glass as an active component of functional materials

Yuanzheng Yue

Section of Chemistry, Aalborg University, Denmark State Key Laboratory of Silicate Materials for Architecture, Wuhan University of Technology, China

Functional glass is the glass exhibiting special physical and chemical performances for various advanced applications. Today many scientists are developing and studying new generations of functional glasses, e.g. photonic, magnetic, conductive, biological glasses. Most of these studies focus on design of glass compositions or post-treatment of glasses under various conditions. However, there are many promising possibilities for glass to be used as an active component in other types of functional materials. This aspect is attracting the attention of scientists. Here we describe this aspect by using some of our recent studies as examples.

(1) Glass is utilized to enhance the chemical reactivity and mechanical performances in cementations materials. The CO_2 emission of cement production is greatly reduced by substituting a mixture of well-designed glass powder and lime powder for part of clinker. At the same time, both pozzolanity and compressive strength of cement are enhanced [1]. We also investigate dental cement consisting of glass powder and polymer with respect to its fracture toughness and bioactivity during setting [2]. It is found that the fracture toughness of the dental cement change is governed by the interface structure between glass and polymer. Using differential scanning calorimetry (DSC) and Nuclear Magnetic resonance we found that the fracture toughness and reactivity of the cement depend on the chemical composition, structure, phase separation, and post-treatment of glass powder.

(2) Disorder concept is applied to improve the performances of lithium ion batteries. The disordered nanostructure provides sites for storing Li^+ ions and easier transfer kinetics of electrons and lithium ions, and displays the superior discharge capacity and an ultra-high coulombic efficiency [3].

(3) Glass is made nanoporous and bioactive to effectively immobilize enzymes for enhancing their catalytic activity [4]. This glass proves to be a crucial component of functional bio-systems, which enables enzyme more efficient for bioconversion, bioremediation, biosensors and drugs.

(4) A new approach is discovered for fabricating polyamorphic organic/inorganic hybrid glasses from a single metal-organic framework (MOF) using DSC. The new approach is based on a well-controlled dynamic heating and cooling processes. Even bulk MOF glass is obtained by cooling the hybrid liquid. This offers an industrially feasible route to functional hybrid glasses from metal-organic frameworks, and gives new ways to understanding the polyamorphic transition and its relation to liquid fragility in MOF materials.

(5) Glassy thin film is generated on a substrate to fabricate membrane devices [5]. It is the glassy film that offers multi-functionalities to membrane. Thus, the glassy film is an active component of functional devices.

References:

[1] M. Moesgaard, D. Herfort, M. Steenberg, L.F. Kirkegaard, Y.Z. Yue, Cem. Concr. Res., 41 (2011) 359-364.

[2] K.V. Tian, et al., Nature Mater. (2014) (under review).

[3] X. D. Zhang, Z.Y. Bi, W. He, G. Yang, H. Liu, Y. Z. Yue, Energy Environ. Sci. (2014) DOI: 10.1039/c3ee44187c.
[4] W. He, D.D. Min, X.D. Zhang, Y. Zhang, Z.Y. Bi, Y. Z. Yue, *Adv. Funct. Mater.* 24 (2014) 2206–2215.

[5] V. Boffa, G. Magnacca, L.B. Jorgensen, A. Wehner, A. Dornhofer, Y.Z. Yue, *Microporous Mesoporous Mater*. **179C** (2013) 242-249.