



AALBORG UNIVERSITY
DENMARK

Aalborg Universitet

Time and Humidity Dependence of Indentation Cracking in Aluminosilicate Glasses

Bechgaard, Tobias Kjær; Mauro, John C.; Smedskjær, Morten Mattrup

DOI (link to publication from Publisher):
[10.1016/j.jnoncrysol.2018.04.009](https://doi.org/10.1016/j.jnoncrysol.2018.04.009)

Publication date:
2018

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Bechgaard, T. K., Mauro, J. C., & Smedskjær, M. M. (2018). *Time and Humidity Dependence of Indentation Cracking in Aluminosilicate Glasses*. 64-70. Poster presented at 2018 Glass and Optical Materials Division Annual Meeting, San Antonio, Texas, United States. <https://doi.org/10.1016/j.jnoncrysol.2018.04.009>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

(GOMD-GSP-P003-2018) Time and Humidity Dependence of Indentation Cracking in Aluminosilicate Glasses

T. K. Bechgaard^{*1}; J. C. Mauro²; M. M. Smedskjaer¹

1. Aalborg University, Denmark 2. Pennsylvania State University, Department of Materials Science and Engineering, USA

The inherent brittleness and poor crack resistance of oxide glasses have always been among their main limitations for advanced applications. As the formation of cracks leads to amplification of applied tensile stresses and ultimately catastrophic failure, there is an interest in understanding the composition and structure dependence of crack initiation and growth. The resistance to cracking can conventionally be measured using instrumented indentation that mimics the real-life damage for certain applications. Wada introduced a method to evaluate the crack resistance by counting the number of initiated cracks as a function of the applied load. Experiments have shown that the environmental humidity and the time period between indentation and crack counting affect the crack resistance value, but unfortunately these parameters are not always reported in literature studies. Here we study the time and humidity dependence of crack initiation in calcium aluminosilicate glasses. Depending on the experimental conditions (time and humidity), the crack resistance of an aluminosilicate glass can vary more than 100%. Furthermore, the observed radial/median cracks can initiate several hours after indentation. These results therefore indicate the need of a standardized procedure for determination of crack resistance to allow comparison of data from different research groups.