



AALBORG UNIVERSITY
DENMARK

Aalborg Universitet

Nanoindentation of Thin Glass Fibers

Lönnroth, Nadja Teresia; Pantano, C.; Yue, Yuanzheng

Publication date:
2005

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Lönnroth, N. T., Pantano, C., & Yue, Y. (2005). *Nanoindentation of Thin Glass Fibers*. Abstract from 3th International Workshop on Flow and Fracture of Advanced Glasses, PennState, USA .

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Nanoindentation of thin glass fibers

N. Lönnroth*, C. Pantano^o and Y. Z. Yue*

*Department of Life Sciences, Section of Chemistry, Aalborg University,
Sohngaardsholmsvej 57, DK-9000 Aalborg, Denmark

^oDepartment of Materials Science and Engineering, Materials Research Institute,
The Pennsylvania State University, University Park, PA 16802, USA

Abstract

Nanoindentation has been used to determine hardness and elastic modulus of glass fibers with diameters in the range of 5-20 μm . The samples include both continuous E-glass fibers and stone wool fibers as well as a bulk basaltic glass sample. By experimenting on mounting techniques and indentation procedures it has been possible to get consistent data on the fiber samples. This provides a direct tool to characterize the intrinsic mechanical properties of thin fibers. Fibers, independent of the composition, show a tendency of increasing hardness (H) and elastic modulus (E) with increasing fiber diameter. This shows that the cooling rate effect on glass structure can be characterized by nanoindentation measurements. Indenting the cast surface of the bulk basaltic glass, shows a surface layer with a depth of 100 nm that has higher H and E than the interior glass. Further experiments are planned to be carried out in order to gain more information and better understanding on the observed phenomena.