



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Analysis of Horizontal Bearing Capacity of Caisson Breakwater

Ibsen, Lars Bo

Publication date:
1998

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Ibsen, L. B. (1998). *Analysis of Horizontal Bearing Capacity of Caisson Breakwater*. Geotechnical Engineering Group. AAU Geotechnical Engineering Papers: Soil Mechanics Paper Vol. R 9802 No. 20

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Analysis of Horizontal Bearing Capacity of Caisson Breakwater

L.B. Ibsen

February 1998

Soil Mechanics Paper No 20



**GEOTECHNICAL ENGINEERING GROUP
AALBORG UNIVERSITY DENMARK**

Ibsen, L.B. (1998). Analysis of Horizontal Bearing Capacity of Caisson Breakwater.

AAU Geotechnical Engineering Papers, ISSN 1398-6465 R9802.

Soil Mechanics Paper No 20

2nd PROVERBS Workshop, Napels, February 24-27-98.

© 1998 AAU Geotechnical Engineering Group.

Except for fair copying, no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of the Geotechnical Engineering Group.

Papers or other contributions in AAU Geotechnical Engineering Papers and the statements made or opinions expressed therein are published on the understanding that the author of the contribution is solely responsible for the opinions expressed in it and that its publication does not necessarily imply that such statements or opinions are or reflect the views of the AAU Geotechnical Engineering Group.

The AAU Geotechnical Engineering Papers - AGEP - are issued for early dissemination and book keeping of research results from the Geotechnical Engineering Group at Aalborg University (Department of Civil Engineering). Moreover, the papers accommodate proliferation and documentation of field and laboratory test series not directly suited for publication in journals or proceedings.

The papers are numbered ISSN 1398-6465 R<two digit year code><two digit consecutive number>. For internal purposes the papers are, further, submitted with coloured covers in the following series:

Series	Colour
Laboratory testing papers	sand
Field testing papers	grey
Manuals & guides	red
Soil Mechanics papers	blue
Foundation Engineering papers	green
Engineering Geology papers	yellow
Environmental Engineering papers	brown

In general the AGEP papers are submitted to journals, conferences or scientific meetings and hence, whenever possible, reference should be given to the final publication (journal, proceeding etc.) and not to the AGEPPaper.

Task report 2.2.d :

Analysis of Horizontal Bearing Capacity of Caisson Breakwater

By
L.B.Ibsen
AAU Geotechnical Engineering Group

In this task report the caisson breakwater structure, which has been tested in the centrifuge at Delft Geotechnics, is modelled in ABAQUS by means of the verified material model subroutine containing the Single Hardening Model. The response of the caisson is investigated under drained as well as undrained conditions. The results from the numerical analysis are compared to results obtained from the centrifuge test, which has been carried out with Eastern Scheldt Sand with $e = 0,67$ as the chosen model soil. Furthermore, an analytical bearing capacity analysis in the shape of an upper bound solution is put forward as a reference for the numerically obtained horizontal bearing capacity. Finally, reference numerical calculations based on the simpler Drucker-Prager Model are brought in for comparison. The performed analysis with the Single Hardening Model and have these analysis are compared, with analytical and the centrifuge test are schematic illustrated in Figure 1. This task report is a summary of the work reported in chapter. 8 /Andersen et all 1998.a/

Analytical Bearing Capacity

On the basis of a kinematically admissible rupture Figure 2, the bearing capacity of the caisson when exposed to a static horizontal load has been determined. In order to account for the curvature of the failure envelope, different combinations of the cohesion and the friction angle have been used in order to obtain the minimum bearing *Figure* capacity. The friction angle used in the upper bound analysis is a reduced friction angle /Hansen, 1991/ introduced in order to account for the fact that the soil is governed by a non-associated flow rule.




Figure 1. Schematic illustration of the performed analysis with the Single Hardening Model and have these ar the comparisons.




Figure 4. Plane friction angle, cohesion and dilation angle as functions of σ_3' .

11,4 m above the sea bed.

The applied strength parameters are illustrated in Figure 4. Thus, for several values of the plane friction angle, the cohesion, and the dilation angle corresponding to different values of σ_3' , have been applied.

It should be mentioned, however that for the calculations based on the bearing capacity formulation of Terzaghi, the plane-friction angle obtained from is used directly, thus without applying equation for reducing the friction angle. The obtained results form the curves illustrated in Figure 5.

It shall be mentioned that the calculations have been continued at higher levels of σ_3' and the tendency of increasing values of the bearing capacity in terms of higher values of σ_3' continues. However, in order to get a clear picture of the location of the minimum, it is chosen to illustrate this particular section of the curves.

The data in connection with the determined minimum horizontal load according to the upper bound solution and the Danish Code are listed in Table 1.

Due to the fact that use has been made of the reduced friction angle in connection with the upper bound solution, it is seen in that a difference is present between the two curves. However, the shapes of the two curves are more or less identical, and for both analytical analyses, a bearing capacity in the range from 1120 - 1150 kN/m has been obtained.




Figure 5. Bearing capacity according to the Danish Code and an upper bound solution as a function of σ_3' .

Table 1. Data concerning the minimum of the horizontal load according to the Danish Code and the upper bound solution.

	ϕ_{pl} [°]	ψ [°]	ϕ_r [°]	c' [kPa]	b_{eff} [m]	H [kN/m]
Danish Code	40.1	-	-	19.9	2.67	1,151
Upper bound solution	39.7	12.4	35.9	22	2.9	1,127

Numerical Analysis of the Caisson Breakwater

In the centrifuge test, the application of the caisson dead load is introduced by means of the acceleration of the centrifuge to the chosen level of gravitational acceleration. This phase has been modelled by means of the Single Hardening Model. It is concluded that the prediction by the Single Hardening Model differs from the test results. However, during the dead load application all deformations are very small, meaning that the uncertainty attached to the determined deformations is considered to be quite significant.

The horizontal loading of the caisson under drained conditions has been predicted by the Single Hardening Model as well as the Drucker-Prager Model, as shown in Figure 6. As input data for the Drucker-Prager Model, relevant combinations of strength- and deformation parameters have been introduced. By means of the Single Hardening Model, the horizontal bearing capacity is predicted to be slightly smaller than the value obtained by the analytical upper bound solution. The predictions based on the Drucker-Prager Model are seen to be very sensitive to the chosen input parameters. Thus, it is possible to obtain a bearing capacity similar to the Single Hardening Model prediction, but a value of around 20 - 25 % higher than the bearing capacity predicted by the Single Hardening Model is just as likely to occur, if another set of parameters is employed. In all cases, the Drucker-Prager Model estimates large deformations compared to the results from the Single Hardening Model analysis.

The response of the caisson when exposed to different load cycles has been analysed by the Single Hardening Model. Furthermore, the influence of the void ratio to the numerical predictions has been analysed. In both cases, reasonable results are obtained.





Figure 6. Predictions of the horizontal loading, performed by the Single Hardening Model and the Drucker Prager Model. These are compared by the analytical bearing capacity.



	Bearing Capacity [kN/m]	Horizontal displacement [kN/m]
Undrained	1,394	0.51
Partly Undrained	1,350	0.53
Centrifuge test	1,440	0.76

Figure 7. Stress-strain curves for undrained and partly undrained analysis. The bearing capacities are compared with the results from the centrifuge test.

The caisson has been subjected to a partly undrained analysis. Thus, the behaviour of the pore water fluid during the horizontal load application has been included in the analysis. This analysis is performed by the Single Hardening Model. The bearing capacity obtained from the partly undrained analysis is compared to the maximum horizontal wave impact force, experienced during the centrifuge test, and a nice correspondence is observed, although the basis of comparison is not totally identical. This is due to the fact that in the centrifuge test, a large number of cycles have been performed before the maximum wave load is reached. Finally, it is observed that the partly undrained bearing capacity is higher than the drained bearing capacity, which is due to the negative pore pressure build-up, which occurs beneath the caisson during a rapid load application.

The rupture zones and the deformation mechanisms obtained from the respective numerical analyses have been investigated. In all cases, a close resemblance with the kinematically admissible rupture figure is present.

As a final remark, the computational consumption of the two investigated constitutive models should be mentioned, as a large difference has been experienced. Thus, an analysis performed by the Single Hardening Model has been found to be considerably more time consuming than the corresponding Drucker-Prager analysis.

AAU Contribution before 1st August 1997

Ibsen L.B, Jacobsen K.P (1997). *Dynamic Bearing Capacity of Caisson Breakwaters Subjected to Impulsive Wave Loading*. 1st PROVERBS Workshop. Las Palmas, Spain 18-23 feb. 1997.

AAU Contribution 1st August 1997 to 31 January 1998

Andersen A. T, Madsen E.B, Schaarup-Jensen A.L, Ibsen L.B, Jacobsen K.P 1998. *Advanced Numerical Analysis of Caisson Breakwater Founded on Frictional Materials*. Research Report by Aalborg University, Geotechnical Engineering Group. co-sponsored by Commission of the European Union Directorate General XII MAST contract MAS3 - CT95 - 0041 (1996 - 1999). 300 pages report. ISBN 87-88787-16-8.

Andersen A. T, Madsen E.B, Schaarup-Jensen A.L 1998. *DATA REPORT 9701 Part 1. Easter Scheldt Sand, Baskarp Sand No.15*. Data Report by Aalborg University, Geotechnical Engineering Group. co-sponsored by Commission of the European Union Directorate General XII MAST contract MAS3 - CT95 - 0041 (1996 - 1999). 55 pages report.

AGEP: Soil Mechanics papers

- 6 Ibsen, L.B. (1995). Soil Parameters, Final proceedings MCS - Project MAST II, July 1995. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9514.
- 7 Sørensen, C. S., Ibsen, L. B. , Jakobsen, F. R., Hansen, A., Jakobsen, K. P., (1995) "Bearing Capacity of Caisson Breakwaters on Rubble Mounds". Proceedings of the Final Project Workshop, Monolithic (Vertical) Coastal Structures, Alderney, UK, Appendix IX, p 26. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9515.
- 8 Ibsen, L.B., Steenfelt, J.S. (1996). Terningapparatet - et middel til bedre jordforståelse (The true-triaxial-apparatus - a means to better understanding of soil behaviour; in Danish). *Proc. Nordic Geotechnical Meeting, NGM-96, Reykjavik, Vol 1*, pp 111-122. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9603.
- 9 Thorsen, G., Thomsen, B., Thorsen, S. (1996). Tilsyneladende forbelastning af Eem jordarter (Apparent preconsolidation of Eemian soils; in Danish). *Proc. Nordic Geotechnical Meeting, NGM-96, Reykjavik, Vol 1*, pp 147-152. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9607.
- 10 Thorsen, G. (1996). Oedometer tests - an aid in determination of the geological load history. *Bull. of the Geological Society of Denmark*, Vol. 43, pp. 41-50. Copenhagen 1996-07-14. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9608.
- 11 Ibsen, L.B., Jakobsen, K.P. (1997). Dynamic Bearing Capacity of Caisson Breakwaters Subjected to Impulsive Wave Loading. MAST III (PROVERBS Workshop, Las Palmas, Feb. 18-24-1997. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9701.
- 12 Lade, P.V., Ibsen, L.B. (1997). A study of the phase transformation and the characteristic lines of sand behaviour. *Proc. Int. Symp. on Deformation and Progressive Failure in Geomechanics, Nagoya, Oct. 1997*, pp. 353-359. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9702.
- 13 Bødker, L., Steenfelt, J.S. (1997). Vurdering af lodrette flytningsamplituder for maskinfundament, Color Print, Vadum (Evaluation of displacement amplitudes for printing machine foundation; in Danish). *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9706.
- 14 Ibsen, L.B., Steenfelt, J.S. (1997). Vurdering af lodrette flytningsamplituder for maskinfundament Løkkensvejens kraftvarmeværk (Evaluation of displacement amplitudes for gas turbine machine foundation; in Danish). *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9707.
- 15 Steenfelt, J.S. (1997). National R&D Report : Denmark. *Seminar on Soil Mechanics and Foundation Engineering R&D*, Delft 13-14 February 1997. pp 4. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9708.
- 16 Lemonnier, P. and Soubra, A. H. (1997). Validation of the recent development of the displacement method - geogrid reinforced wall. *Colloquy EC97 on the comparison between experimental and numerical results*, Strasbourg, France. Vol.1, pp. 95-102. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9712.

AGEP: Soil Mechanics papers

- 17 Lemonnier, P. & Soubra, A. H. (1997). Recent development of the displacement method for the design of geosynthetically reinforced slopes - Comparative case study. *Colloquy on geosynthetics, Rencontres97, CFG*, Reims, France, Vol. 2, pp. 28AF-31AF (10pp). Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9713.
- 18 Lemonnier, P., Soubra, A. H. & Kastner, R. (1997). Variational displacement method for geosynthetically reinforced slope stability analysis : I. Local stability. *Geotextiles and Geomembranes* 16 (1998) pp 1-25. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9714.
- 19 Lemonnier, P., Soubra, A. H. & Kastner, R. (1997). Variational displacement method for geosynthetically reinforced slope stability analysis : II. Global stability. *Geotextiles and Geomembranes* 16 (1998) pp 27-44. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9715.
- 20 Ibsen, L.B. (1998). Analysis of Horizontal Bearing Capacity of Caisson Breakwater. 2nd PROVERS Workshop, Napels, Italy, Feb. 24-27-98. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9802.
- 21 Ibsen, L.B. (1998). Advanced Numerical Analysis of Caisson Breakwater. *2nd PROVERS Workshop*, Napels, Italy, Feb. 24-27-98. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9803.
- 22 Ibsen, L.B., Lade P.V. (1998). The Role of the Characteristic Line in Static Soil Behavior. *Proc. 4th International Workshop on Localization and Bifurcation Theory for Soil and Rocks*. Gifu, Japan. Balkema 1998. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9804.
- 23 Ibsen, L.B., Lade, P.V. (1998). The Strength and Deformation Characteristics of Sand Beneath Vertical Breakwaters Subjected to Wave Loading. 2nd PROVERS Workshop, Napels, Italy, Feb. 24-27-98. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9805.
- 24 Steenfelt, J.S., Ibsen, L.B. (1998). The geodynamic approach - problem or possibility? Key Note Lecture, *Proc. Nordic Geotechnical Meeting, NGM-96, Reykjavik*, Vol 2, pp 14. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9809.
- 25 Lemonnier, P., Gotteland, Ph. and Soubra, A. H. (1998). Recent developments of the displacement method. *Proc. 6th Int. Conf. on Geosynthetics. Atlanta, USA*, Vol 2, pp 507-510. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9814.
- 26 Praastrup, U., Jakobsen, K.P., Ibsen, L.B. (1998). On the choice of strain measures in geomechanics. 12th Young Geotechnical Engineers Conference, Tallin, Estonia. *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9815.
- 27 Ibsen, L.B. (1998). The mechanism controlling static liquefaction and cyclic strength of sand. *Proc. Int. Workshop on Physics and Mechanics of Soil Liquefaction*, Baltimore. A.A.Balkema, ISBN 9058090388, pp 29-39. Also in *AAU Geotechnical Engineering Papers*, ISSN 1398-6465 R9816.