



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Small-Scale Cyclic Tests on Non slender Piles Situated in Sand

test results

Sørensen, Søren Peder Hyldal; Ibsen, Lars Bo

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):
Sørensen, S. P. H., & Ibsen, L. B. (2011). *Small-Scale Cyclic Tests on Non slender Piles Situated in Sand: test results*. Department of Civil Engineering, Aalborg University. DCE Technical reports No. 118

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.


- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Small-scale cyclic tests on non-slender piles situated in sand – Test results

Søren Peder Hyldal Sørensen
Lars Bo Ibsen



Aalborg University
Department of Civil Engineering
Geotechnical Engineering Research Group

DCE Technical Report No. 118

Small-scale cyclic tests on non-slender piles situated in sand – Test results

by

Søren Peder Hyldal Sørensen
Lars Bo Ibsen

October 2011

© Aalborg University

Scientific Publications at the Department of Civil Engineering

Technical Reports are published for timely dissemination of research results and scientific work carried out at the Department of Civil Engineering (DCE) at Aalborg University. This medium allows publication of more detailed explanations and results than typically allowed in scientific journals.

Technical Memoranda are produced to enable the preliminary dissemination of scientific work by the personnel of the DCE where such release is deemed to be appropriate. Documents of this kind may be incomplete or temporary versions of papers—or part of continuing work. This should be kept in mind when references are given to publications of this kind.

Contract Reports are produced to report scientific work carried out under contract. Publications of this kind contain confidential matter and are reserved for the sponsors and the DCE. Therefore, Contract Reports are generally not available for public circulation.

Lecture Notes contain material produced by the lecturers at the DCE for educational purposes. This may be scientific notes, lecture books, example problems or manuals for laboratory work, or computer programs developed at the DCE.

Theses are monographs or collections of papers published to report the scientific work carried out at the DCE to obtain a degree as either PhD or Doctor of Technology. The thesis is publicly available after the defence of the degree.

Latest News is published to enable rapid communication of information about scientific work carried out at the DCE. This includes the status of research projects, developments in the laboratories, information about collaborative work and recent research results.

Published 2011 by
Aalborg University
Department of Civil Engineering
Sohngaardsholmsvej 57,
DK-9000 Aalborg, Denmark

Printed in Aalborg at Aalborg University

ISSN 1901-726X
DCE Technical Report No. 118

Small-scale cyclic tests on non-slender piles situated in sand – Test results

Contents

Introduction.....	7
References.....	8
Soil parameters and test results.....	9
Test 1: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 0$ kPa (Closed-ended)	11
Test 2: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 50$ kPa (Closed-ended)	15
Test 3: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 100$ kPa (Closed-ended)	19
Test 4: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 0$ kPa (Closed-ended)	23
Test 5: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 50$ kPa (Closed-ended)	27
Test 6: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 100$ kPa (Closed-ended)	31
Test 7: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 0$ kPa (Closed-ended)	35
Test 8: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 25$ kPa (Closed-ended)	39
Test 9: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 50$ kPa (Closed-ended)	43
Test 10: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 75$ kPa (Closed-ended)	47
Test 11: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 100$ kPa (Closed-ended)	51
Test 12: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 0$ kPa (Closed-ended)	55
Test 13: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 50$ kPa (Closed-ended)	59
Test 14: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 100$ kPa (Closed-ended)	63
Test 15: $D = 100$ mm, $L_p = 500$ mm and $P_0 = 0$ kPa (Closed-ended)	67
Comparison with quasi-static tests	71
<i>Load-displacement relationships</i>	73
Acknowledgements	79

Introduction

In the period from August 2011 till October 2011 a series of small-scale tests on pile foundations has been conducted at Aalborg University. In all the tests, the piles have been exposed to cyclic loading consisting of 20-25 load cycles and all the tests have been conducted in a pressure tank. The objective of the tests has been to investigate the effect of pile diameter, length to diameter ratio and cyclic loading on the soil response for non-slender piles in sand.

Piles with outer diameters, D , varying between 80 and 100 mm, pile embedment lengths, L_p , between 240 and 500 mm and length to diameter ratios (slenderness ratios), L_p/D , from 3 to 6 have been tested. Hereby, the scales of the tested piles are approximately between 1:40 and 1:80 of a full-scale monopile foundation for an offshore wind turbine.

One of the significant uncertainties when conducting small-scale tests is that the stresses in the soil are small when comparing to a full-scale pile. As the soil parameters depend on the stress level this leads to uncertainties when trying to scale the small-scale tests to a full-scale monopile foundation. Further, the determination of the soil parameters is uncertain for low stress levels. When conducting the tests in a pressure tank it is possible to add an excess pressure (overburden pressure), P_0 . In order to increase the effective stresses in the soil, and not the pore pressure, a membrane have been placed on top of the soil for the tests conducted with overburden pressure. The overburden pressure has been varied between 0 and 100 kPa. An overburden pressure of 100 kPa corresponds to the effective vertical stress in the soil at a depth of approximately 10 m.

The test setup and the preparation prior to testing are similar to the quasi-static tests on laterally loaded piles described in Sørensen and Ibsen (2011). The test setup and preparation prior to testing is therefore not described in this report. In order to apply two-way loading to the test piles an aluminium bar has been positioned between the hydraulic piston and the pile. In the tests described by Sørensen and Ibsen (2011) a steel wire was used.

The test programme is shown in Table 1.

TABLE 1. TEST PROGRAMME. SG DENOTES STRAIN GAUGES.

Test	Pile diameter, D [mm]	Embedded pile length, L [mm]	Pile slenderness ratio, L/D [-]	Overburden pressure, P_0 [kPa]	Number of strain gauges measuring
1	80	240	3	0	0
2	80	240	3	50	0
3	80	240	3	100	0
4	80	320	4	0	11
5	80	320	4	50	11
6	80	320	4	100	11
7	80	400	5	0	11
8	80	400	5	25	11
9	80	400	5	50	11
10	80	400	5	75	11
11	80	400	5	100	11
12	80	480	6	0	11
13	80	480	6	50	11
14	80	480	6	100	11
15	100	500	5	0	0

References

Sørensen, S. P. H. & Ibsen, L. B. 2011. Small-scale quasi-static tests on non-slender piles situated in sand – Test results. *DCE Technical Report No. 112, Department of Civil Engineering, Aalborg University, Denmark.*

Soil parameters and test results

In the following the test results for the 29 conducted tests are presented. The results and interpretation of the conducted CPT's prior to each test is presented. Further, the direct measurements from the tests are presented. For the tests with strain gauges attached the distribution of pile displacement, pile rotation, pile curvature, pile bending moment and soil resistance with depth and furthermore p - y curves determined based on the direct measurements are shown.

Test 1: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 0$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 10/11-2011
Pile diameter (mm): 80	No. of strain gauge levels: 0
Embedded pile length (mm): 240	Overburden pressure (kPa): 0
Slenderness ratio, L/D: 3	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments:	

Soil parameters:

TABLE 2. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.75-0.91	52.0-54.5	17.4-20.5	10.1-10.4	-	0.23

Test results:




FIGURE 1. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT.

Test 2: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 50$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 7/10-2011
Pile diameter (mm): 80	No. of strain gauge levels: 0
Embedded pile length (mm): 240	Overburden pressure (kPa): 50
Slenderness ratio, L/D: 3	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of 8 l/h.	

Soil parameters:

TABLE 3. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.75-0.91	48.0-51.0	16.3-19.5	10.1-10.4	23.6-31.8	0.23

Test results:




FIGURE 2. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 3: $D = 80$ mm, $L_p = 240$ mm and $P_0 = 100$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 9/10-2011
Pile diameter (mm): 80	No. of strain gauge levels: 0
Embedded pile length (mm): 240	Overburden pressure (kPa): 100
Slenderness ratio, L/D: 3	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments:	

Soil parameters:

TABLE 4. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.75-0.91	45.3-48.1	15.4-18.6	10.1-10.4	37.8-51.5	0.23

Test results:




FIGURE 3. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 4: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 0$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 23/9-2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 320	Overburden pressure (kPa): 0
Slenderness ratio, L/D: 4	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas & S. P. H. Sørensen
Comments:	

Soil parameters:




FIGURE 4. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 5. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.78	52.7	18.0	10.2	-	0.23

Test results:




FIGURE 5. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT.

Test 5: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 50$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 25/9-2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 320	Overburden pressure (kPa): 50
Slenderness ratio, L/D: 4	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments:	

Soil parameters:




FIGURE 6. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 6. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.82	49.4	17.7	10.3	27.3	0.23

Test results:




FIGURE 7. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 6: $D = 80$ mm, $L_p = 320$ mm and $P_0 = 100$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 2/10-2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 320	Overburden pressure (kPa): 100
Slenderness ratio, L/D: 4	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of 8 l/h.	

Soil parameters:




FIGURE 8. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 7. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.82	46.5	16.7	10.3	42.5	0.23

Test results:




FIGURE 9. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 7: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 0$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: Summer 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 400	Overburden pressure (kPa): 0
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments:	

Soil parameters:




FIGURE 10. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 8. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.77	52.5	17.8	10.2	-	0.23

Test results:




FIGURE 11. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT.

Test 8: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 25$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 1/9 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 400	Overburden pressure (kPa): 25
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 2-3 l/hour.	

Soil parameters:




FIGURE 12. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 9. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.79	52.2	18.1	10.2	15.6	0.23

Test results:




FIGURE 13. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 9: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 50$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 22/8 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 400	Overburden pressure (kPa): 50
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 6 l/hour.	

Soil parameters:




FIGURE 14. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 10. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.77	48.3	16.7	10.2	24.7	0.23

Test results:




FIGURE 15. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 10: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 75$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 30/8 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 400	Overburden pressure (kPa): 75
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 6-10 l/hour. The screw attaching the force transducer to the hydraulic piston was loose. Therefore the displacement pattern of the pile was not as desired.	

Soil parameters:




FIGURE 16. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 11. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.81	47.4	17.0	10.2	35.4	0.23

Test results:




FIGURE 17. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 11: $D = 80$ mm, $L_p = 400$ mm and $P_0 = 100$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 29/8 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 400	Overburden pressure (kPa): 100
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 9 l/hour. The screw attaching the force transducer to the hydraulic piston was loose. Therefore the displacement pattern of the pile was not as desired.	

Soil parameters:




FIGURE 18. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 12. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.80	46.2	16.5	10.2	42.2	0.23

Test results:




FIGURE 19. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 12: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 0$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 18/9 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 480	Overburden pressure (kPa): 0
Slenderness ratio, L/D: 6	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Strain gauge 1 did not work.	

Soil parameters:




FIGURE 20. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 13. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.81	53.0	18.5	10.2	-	0.23

Test results:




FIGURE 21. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT.

Test 13: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 50$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 7/9 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 480	Overburden pressure (kPa): 50
Slenderness ratio, L/D: 6	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 5 l/hour. The screw attaching the force transducer to the hydraulic piston was loose. Therefore the displacement pattern of the pile was not as desired.	

Soil parameters:




FIGURE 22. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 14. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.82	49.0	17.5	10.2	26.9	0.23

Test results:




FIGURE 23. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 14: $D = 80$ mm, $L_p = 480$ mm and $P_0 = 100$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: 11/9 2011
Pile diameter (mm): 80	No. of strain gauge levels: 11(All below soil surface)
Embedded pile length (mm): 480	Overburden pressure (kPa): 100
Slenderness ratio, L/D: 6	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: L. Mikalauskas
Comments: Water flow of approximately 15 l/hour. The screw attaching the force transducer to the hydraulic piston was loose. Therefore the displacement pattern of the pile was not as desired. The pile was moved vertically 1 cm prior to the test.	

Soil parameters:




FIGURE 24. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 15. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.79	46.0	16.2	10.2	41.2	0.23

Test results:




FIGURE 25. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT – BOTTOM LEFT: TANK PRESSURE VERSUS TIME.

Test 15: $D = 100$ mm, $L_p = 500$ mm and $P_0 = 0$ kPa (Closed-ended)

Pile type: Closed-ended	Completed: Summer 2011
Pile diameter (mm): 100	No. of strain gauge levels: 0 (All below soil surface)
Embedded pile length (mm): 500	Overburden pressure (kPa): 0
Slenderness ratio, L/D: 5	Load eccentricity (mm): 370
Pile wall thickness (mm): 5	By: S. P. H. Sørensen and L. Mikalauskas
Comments: A maximum was set for the size of the output file causing the test to stop twice. After each stop the pile displacement started from zero.	

Soil parameters:




FIGURE 26. CPT-RESULTS. LEFT: TIP RESISTANCE VERSUS DEPTH – RIGHT: RELATIVE DENSITY VERSUS DEPTH.

TABLE 16. ESTIMATED SOIL PARAMETERS.

Relative density, I_D	Internal friction angle, φ_{tr}	Dilatancy angle, ψ_{tr}	Effective unit weight, γ'	Tangential Young's modulus of elasticity, E_0	Poisson's ratio, ν
[-]	[°]	[°]	[kN/m ³]	[MPa]	[-]
0.85	53.6	19.4	10.3	-	0.23

Test results:




FIGURE 27. TOP LEFT: PILE DISPLACEMENT VERSUS TIME – TOP RIGHT: HORIZONTAL LOAD VERSUS TIME – CENTER LEFT: HORIZONTAL LOAD VERSUS PILE DISPLACEMENT – CENTER RIGHT: PEAK HORIZONTAL LOAD VERSUS PEAK HORIZONTAL DISPLACEMENT.

Comparison with quasi-static tests

In the following the load-displacement relationships from the cyclic small-scale tests are compared with the quasi-static small-scale tests conducted by Sørensen and Ibsen (2011). Both test series have been conducted in a pressure tank at Aalborg University. The only differences between the tests is the applied loading and that a wire was used to attach the pile to the hydraulic piston for the quasi-static tests while a bar was used for the cyclic tests hereby enabling two-way loading.

Load-displacement relationships




FIGURE 28. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 240$ mm, $P_0 = 0$ kPa.




FIGURE 29. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 240$ mm, $P_0 = 50$ kPa.




FIGURE 30. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 240$ mm, $P_0 = 100$ kPa.




FIGURE 31. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 320$ mm, $P_0 = 0$ kPa.




FIGURE 32. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 320$ mm, $P_0 = 50$ kPa.




FIGURE 33. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 320$ mm, $P_0 = 100$ kPa.




FIGURE 34. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 400$ mm, $P_0 = 0$ kPa.




FIGURE 35. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 400$ mm, $P_0 = 25$ kPa.




FIGURE 36. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80 \text{ mm}$, $L_p = 400 \text{ mm}$, $P_0 = 50 \text{ kPa}$.




FIGURE 37. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80 \text{ mm}$, $L_p = 400 \text{ mm}$, $P_0 = 75 \text{ kPa}$.




FIGURE 38. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80 \text{ mm}$, $L_p = 400 \text{ mm}$, $P_0 = 100 \text{ kPa}$.




FIGURE 39. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 480$ mm, $P_0 = 0$ kPa.




FIGURE 40. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 480$ mm, $P_0 = 50$ kPa.




FIGURE 41. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 80$ mm, $L_p = 480$ mm, $P_0 = 100$ kPa.




FIGURE 42. COMPARISON OF THE LOAD-DISPLACEMENT RELATIONSHIP FROM THE CYCLIC TESTS WITH THE QUASI-STATIC TESTS. $D = 100$ mm, $L_p = 500$ mm, $p_0 = 0$ kPa.

Acknowledgements

The experimental work has only been possible with the financial support from the Energy Research Programme administered by the Danish Energy Authority. The experimental work is associated with the ERP programme “Physical and numerical modelling of monopile for offshore wind turbines”, journal no. 033001/33033-0039. The funding is sincerely acknowledged. Appreciation is extended to Linas Mikalauskas for helping with the experimental work. Furthermore, the authors would like to thank the staff at the laboratory at the Department of Civil Engineering, Aalborg University, for their immeasurable help with the test setup.

Recent publications in the DCE Technical Report Series

Brødbæk K. T., Møller M., Sørensen S. P. H. & Augustesen A. H. 2009. Review of p-y relationships in cohesionless soil. *DCE Technical Report No. 57, Aalborg University, Denmark.*

Sørensen S. P. H., Møller M., Brødbæk K. T., Augustesen A. H. & Ibsen L. B. 2009. Evaluation of Load-Displacement Relationships for Non-Slender Monopiles in Sand. *DCE Technical Report No. 79, Aalborg University, Denmark.*

Sørensen S. P. H., Møller M., Brødbæk K. T., Augustesen A. H. & Ibsen L. B. 2009. Numerical Evaluation of Load-Displacement Relationships for Non-Slender Monopiles in Sand. *DCE Technical Report No. 80, Aalborg University, Denmark.*

Sørensen S. P. H. & Ibsen L. B. 2011. Small-scale quasi-static tests on non-slender piles in sand – Test results. *DCE Technical Report No. 112, Aalborg University, Denmark.*

Thomassen K., Roesen H. R., Ibsen L. B. & Sørensen S. P. H. 2010. Small-Scale Testing of Laterally Loaded Non-Slender Monopiles in Sand. *DCE Technical Report No. 90, Aalborg University, Denmark.*

Thomassen K., Roesen H. R., Ibsen L. B. & Sørensen S. P. H. 2010. Evaluation of Small-Scale Laterally Loaded Non-Slender Monopiles in Sand. *DCE Technical Report No. 91, Aalborg University, Denmark.*

