



AALBORG UNIVERSITY
DENMARK

Aalborg Universitet

Approximation with wave packets generated by a refinable function

Borup, Lasse; Nielsen, Morten

Published in:
Proceedings of the American Mathematical Society

Publication date:
2005

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):
Borup, L., & Nielsen, M. (2005). Approximation with wave packets generated by a refinable function. *Proceedings of the American Mathematical Society*, 133(8), 2409-2418.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Approximation with wave packets generated by a refinable function

Abstract: We consider best m -term approximation in $L_p(\mathbb{R}^d)$ with wave packets generated by a single refinable function. The main examples of wave packets are orthonormal wavelets, or more generally wavelet frames based on a multiresolution analysis (so-called framelets). The approximation classes associated with best m -term approximation in $L_p(\mathbb{R}^d)$ for a large class of wave packets are completely characterized in terms of Besov spaces.

As an application of the main result, we show that for m -term approximation in $L_p(\mathbb{R}^d)$ with elements from an oversampled version of a framelet system with compactly supported generators, the associated approximation classes turn out to be (essentially) Besov spaces.