



AALBORG UNIVERSITY
DENMARK

Aalborg Universitet

What happens on the surface of basaltic glass fibers during heat treatment?

Smedskjær, Morten Mattrup; Yue, Yuanzheng; Solvang, Mette

Published in:

International Glass Fiber Symposia 2012: Proceedings of the first International Symposium on Glass Fiber

Publication date:
2012

Document Version
Early version, also known as pre-print

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Smedskjær, M. M., Yue, Y., & Solvang, M. (2012). What happens on the surface of basaltic glass fibers during heat treatment? In *International Glass Fiber Symposia 2012: Proceedings of the first International Symposium on Glass Fiber* (pp. 74). Institut für Textiltechnik of RWTH Aachen University.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

What happens on the surface of basaltic glass fibers during heat treatment?

Morten M. Smedskjaer¹, Yuanzheng Yue¹, Mette Solvang²

¹ *Section of Chemistry, Aalborg University, Denmark*

² *Rockwool International A/S, Denmark*

Basaltic wool fibers (iron-rich aluminosilicate glasses) are used as heat and acoustic insulation material and fire barrier due to their excellent high temperature stability (HTS). We investigate the origins of the HTS of these glass fibers under different atmospheres. We show that the HTS is strongly related with diffusion processes that occur in the fiber surface layer during heat-treatment. The diffusion processes are in turn a result of the iron redox reactions under both oxidizing and reducing conditions. A modifier-rich MgO layer is created during thermal oxidation, whereas a modifier-depleted SiO₂ layer is created during thermal reduction. These layers have different influences on the crystallization behavior and chemical and mechanical properties of the fibers.