

Lumped-Parameter Models for Wind-Turbine Footings on Layered Ground

Andersen, Lars; Liingaard, Morten

Published in:

Proceedings of the Eleventh International Conference on Civil, Structural and Environmental Engineering Computing

Publication date:

2007

Document Version

Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Andersen, L., & Liingaard, M. (2007). Lumped-Parameter Models for Wind-Turbine Footings on Layered Ground. In *Proceedings of the Eleventh International Conference on Civil, Structural and Environmental Engineering Computing* Civil-Comp Press.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.



The Eleventh International Conference on Civil, Structural and Environmental Engineering Computing



Paper 227

Lumped-Parameter Models for Wind-Turbine Footings on Layered Ground

L. Andersen¹ and M.A. Liingard²

¹Department of Civil Engineering, Aalborg University, Denmark

²DONG Energy A/S, Fredericia, Denmark

Keywords: wind turbines, foundations, impedance, lumped-parameter models, layered soil.

full paper (pdf) - reference

Proceedings

- home
- preface
- contents
- authors
- keywords
- copyright
- reference

©2007 Civil-Comp Ltd
CDROM ISBN
978-1-905088-16-4

Over the last decades, wind turbines have increased significantly in size. Optimisation of the turbine blades and towers has led to slender and therefore extremely flexible structures. Consequently, the first modes of resonance of the total structure are close to the excitation frequencies related to environmental loads from wind and waves. Hence, a modern wind turbine undergoes large deformations, not only during extreme weather conditions but also during power production.

Aeroelastic codes have been developed that may be employed for a lifetime analysis of the structural response. Existing codes, e.g. HAWC [1], have about 30 degrees of freedom for the entire structure. However, the current models do not account for dynamic soil-structure interaction (SSI) and, as a result of this, the forces on the structure may be over- or underestimated. In this paper, the SSI is introduced by fitting a lumped-parameter model [2] to the results of a rigorous model of a layered half-space, using the method proposed by Andersen and Clausen [3].

The influence of the subsoil on the response of a wind turbine is discussed with focus on horizontal excitation of the structure. Two different sites are considered--one with a loose top layer of sand and one with a soft clay deposit at intermediate depth. The emphasis is put on the geometrical damping in the soil, and a parameter study is performed with respect to the layer depths and the material properties of the soil. To ensure realistic results, the dynamic properties of the simple model are based on field measurements on a 3 MW wind turbine in Frederikshavn, Denmark [4].

The main conclusion is that the first mode of resonance, typically about 0.3 Hz, is not influenced by geometrical dissipation in the ground. On the other hand the geometrical damping may have a significant impact on vibrations at the second resonance frequency of the turbine tower, typically about 2 Hz. Here, it makes a great difference whether the soil is drained or undrained. However, the properties of the soil at depths greater than the characteristic length (e.g. diameter) of the foundation have almost no effect on the response.

References

- 1 T.J. Larsen and A.M. Hansen.
"Aeroelastic effects of large blade deflections for wind turbines", in "The Science of Making Torque from Wind", Delft University of Technology (Editor), pages 238-246, Roskilde, Denmark, 2004.
- 2 J.P. Wolf, "Foundation Vibration Analysis Using Simple Physical Models", Prentice-Hall, Englewood Cliffs, NJ, 1994.
- 3 L. Andersen and J. Clausen.
"Impedance of Surface Footings on Layered Ground", in "Proceedings of the Tenth International Conference on Civil, Structural and Environmental Engineering Computing", B.H.V. Topping (Editor), Stirling, United Kingdom, Civil-Comp Press, Paper 255, 2005
- 4 L.B. Ibsen and M. Liingard.
"Output-only modal analysis used on new foundation concept for offshore wind turbine", in "Proceedings of the 1st International Operational Modal Analysis Conference (IOMAC)", Copenhagen, Denmark, 27 April 2005.

St. Julians, Malta, 18-21 September 2007