



AALBORG UNIVERSITY
DENMARK

Aalborg Universitet

A Low Cost Calibration Method for Urban Drainage Models

Rasmussen, Michael R.; Thorndahl, Søren; Schaarup-Jensen, Kjeld

Published in:

Book of Abstracts : 11 ICUD : 31 August - 5 September 2008

Publication date:

2008

Document Version

Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Rasmussen, M. R., Thorndahl, S., & Schaarup-Jensen, K. (2008). A Low Cost Calibration Method for Urban Drainage Models. In *Book of Abstracts : 11 ICUD : 31 August - 5 September 2008: 11th International Conference on Urban Drainage, Edinburgh International Conference Centre, Scotland* (pp. 104)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

A low cost calibration method for urban drainage models

Michael R Rasmussen, Søren Thorndahl, Kjeld Schaarup-Jensen
Presented by - Michael Robdrup Rasmussen, DENMARK

The calibration of the hydrological reduction coefficient is examined for a small catchment. The objective is to determine the hydrological reduction coefficient, which is used for describing how much of the precipitation which falls on impervious areas, that actually ends up in the sewer. The reduction coefficient is found on basis of a combination of a urban drainage model (MOUSE) and a set of simple switches located in a combined sewer overflow (CSO) structure. By calibrating the model with only the duration of the CSO, it was possible to calculate a hydrological reduction coefficient close to what can be found with intensive in-sewer measurement of rain and runoff. The results also clearly indicate that there is a large variation in hydrological reduction coefficient between different rain events.