

Path Integration Applied to Structural Systems with Uncertain Properties

Nielsen, Søren R.K.; Köylüoglu, H. Ugur

Publication date:
1996

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):
Nielsen, S. R. K., & Köylüoglu, H. U. (1996). *Path Integration Applied to Structural Systems with Uncertain Properties*. Dept. of Building Technology and Structural Engineering. Structural Reliability Theory Vol. R9602 No. 150

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

INSTITUTTET FOR BYGNINGSTEKNIK

DEPT. OF BUILDING TECHNOLOGY AND STRUCTURAL ENGINEERING
AALBORG UNIVERSITET • AUC • AALBORG • DANMARK

STRUCTURAL RELIABILITY THEORY PAPER NO. 150

To be presented at the ASCE Joint Specialty Conference on Probabilistic Mechanics and Structural Reliability, Worcester, USA, August 1996

S. R. K. NIELSEN & H. U. KÖYLÜOĞLU
PATH INTEGRATION APPLIED TO STRUCTURAL SYSTEMS WITH UNCERTAIN PROPERTIES

MARCH 1996

ISSN 1395-7953 R9602

The STRUCTURAL RELIABILITY THEORY papers are issued for early dissemination of research results from the Structural Reliability Group at the Department of Building Technology and Structural Engineering, University of Aalborg. These papers are generally submitted to scientific meetings, conferences or journals and should therefore not be widely distributed. Whenever possible reference should be given to the final publications (proceedings, journals, etc.) and not to the Structural Reliability Theory papers.

INSTITUTTET FOR BYGNINGSTEKNIK
DEPT. OF BUILDING TECHNOLOGY AND STRUCTURAL ENGINEERING
AALBORG UNIVERSITET • AUC • AALBORG • DANMARK

STRUCTURAL RELIABILITY THEORY
PAPER NO. 150

To be presented at the ASCE Joint Specialty Conference on Probabilistic Mechanics and Structural Reliability, Worcester, USA, August 1996

S. R. K. NIELSEN & H. U. KÖYLÜOĞLU
PATH INTEGRATION APPLIED TO STRUCTURAL SYSTEMS WITH UN-
CERTAIN PROPERTIES
MARCH 1996

ISSN 1395-7953 R9602

PATH INTEGRATION APPLIED TO STRUCTURAL SYSTEMS WITH UNCERTAIN PROPERTIES

Søren R. K. Nielsen¹ and H. Uğur Köylüoğlu²

ABSTRACT

Path integration (cell-to-cell mapping) method is applied to evaluate the joint probability density function (jpdf) of the response of structural systems, with uncertain properties, subject to white noise excitation. A general methodology to deal with uncertainties is outlined and applied to the friction controlled slip of a structure on a foundation where the friction coefficient is modelled as a random variable. Exact results derived using the total probability theorem are compared to the ones obtained via path integration.

INTRODUCTION

Path integration is an approximate method to solve the Fokker-Planck equation of nonlinear dynamic systems driven by excitations with independent increments. Path integration methods have been applied to nonlinear dynamic systems subject to white noise by Sun and Hsu (1990), Naess and Johnsen (1991), Poisson driven train of impulses Köylüoğlu et al. (1995.a). In all of these studies, very accurate results are reported and it is pointed out that the path integration methods can only be applied to problems of low dimensionality due to the large memory and cpu time requirements of the numerical calculations.

In this paper, new equations are introduced to represent the random variables that model the uncertain properties. A deterministic system equation but with random initial conditions is then obtained for the integrated state vector made up of the displacement, velocity and random variables. Assuming that the random parameters are stochastically independent of the white noise excitation, the integrated state vector becomes Markovian, which further simplifies the problem. Then, the Chapman-Kolmogorov equation is discretized in space and time, and the Markov process is represented by a Markov chain. The proposed method has been applied to the friction controlled slip of a structure on a foundation where the friction coefficient is modelled as a random variable. The transitional probability matrix is calculated numerically using Gaussian closure applied for a small time step.

2. DEALING WITH UNCERTAIN PROPERTIES

The equation of motion of a SDOF system with mass m and random stiffness and damping subject to Gaussian white noise $W(t)$ with intensity S_0 reads in state vector

¹Aalborg University, DK-9000 Aalborg, Denmark.

²Koç University, TR-80860 İstinye, İstanbul, Turkey.

form as

$$\dot{\mathbf{Z}}(t) = \mathbf{a}(\mathbf{Z}(t)) + \mathbf{b}(t)W(t) \quad , \quad \mathbf{Z}(0) = \mathbf{Z}_0 \quad (1)$$

The state vector $\mathbf{Z}(t)$, drift-vector $\mathbf{a}(\mathbf{Z}(t))$ and diffusion vector $\mathbf{b}(t)$ are given as

$$\dot{\mathbf{Z}}(t) = \begin{bmatrix} Y(t) \\ \dot{Y}(t) \\ \mathbf{V}(t) \end{bmatrix} \quad , \quad \mathbf{Z}_0 = \begin{bmatrix} 0 \\ 0 \\ \mathbf{X} \end{bmatrix} \quad , \quad \mathbf{a}(\mathbf{Z}(t)) = \begin{bmatrix} \dot{Y}(t) \\ -\frac{1}{m}H(Y, \dot{Y}, \mathbf{V}) \\ \mathbf{0} \end{bmatrix} \quad , \quad \mathbf{b}(t) = \begin{bmatrix} 0 \\ \frac{1}{m} \\ \mathbf{0} \end{bmatrix} \quad (2)$$

where $H(Y, \dot{Y}, \mathbf{X})$ is the nonlinear restoring force depending on the displacement $Y(t)$, velocity $\dot{Y}(t)$ and mean-zero random variables $\mathbf{X}^T = [X_1, X_2, \dots, X_d]$ specifying the stiffness and damping properties. \mathbf{X} is assumed to be stochastically independent of the white noise excitation $W(t)$, and the jpdf $f_{\mathbf{X}}(\mathbf{x})$ is known. In (1), the random parameters have been introduced as extra state variables $\mathbf{V}(t)$ by the equation $\dot{\mathbf{V}}(t) = \mathbf{0}$, $\mathbf{V}(0) = \mathbf{X}$. Then, the equation of motion with random parameters \mathbf{X} and deterministic initial conditions $Y(0) = \dot{Y}(0) = 0$ has been transformed into an equivalent system with deterministic coefficients and random initial conditions. Due to the white noise excitation and as \mathbf{Z}_0 is independent of $W(t)$, the state vector $\mathbf{Z}(t)$ of dimension $N = 2 + d$ is Markovian. Such a treatment has been investigated in Köylüoğlu et al. (1995.b).

3. PATH INTEGRATION

Let $q_{\mathbf{Z}}(\mathbf{z}, t_i | \mathbf{z}_0, t_{i-1})$ signify the transitional jpdf of the Markov process from the state \mathbf{z}_0 at time t_{i-1} to a state \mathbf{z} at a later time t_i after the i th transition. The jpdf $f_{\mathbf{Z}}(\mathbf{z}, t_i)$ of $\mathbf{Z}(t_i)$ at time t_i then fulfills the Chapman-Kolmogorov equation :

$$f_{\mathbf{Z}}(\mathbf{z}, t_i) = \int_{\mathbf{z}_0} q_{\mathbf{Z}}(\mathbf{z}, t_i | \mathbf{z}_0, t_{i-1}) f_{\mathbf{Z}}(\mathbf{z}_0, t_{i-1}) d\mathbf{z}_0 \quad , \quad i = 1, 2, \dots \quad , \quad t_0 = 0 \quad (3)$$

The initial distribution at time $t = 0$ is given as $f_{\mathbf{Z}}(\mathbf{z}, 0) = f_{Y\dot{Y}\mathbf{V}}(y, \dot{y}, \mathbf{v}, 0) = \delta(y)\delta(\dot{y})f_{\mathbf{X}}(\mathbf{v})$. Path integration demands a suitable discretization of the state space, and constant time intervals $\Delta t = t_i - t_{i-1}$ between the transitions. Then, the time and space continuous Markov vector $\mathbf{Z}(t)$ is carried into a Markov chain with the transition equation

$$\mathbf{p}_i = \mathbf{Q}\mathbf{p}_{i-1} \quad (4)$$

Using a uniform mesh, the j th component $p_{i,j} = \int_{\Delta \mathbf{z}_j} f_{\mathbf{Z}}(\mathbf{z}, t_i) d\mathbf{z}$ of \mathbf{p}_i of (4) being the probability lumped to the j th nodal point with position \mathbf{z}_j , centered in a cell $\Delta \mathbf{z}_j = \Delta z_1 \cdots \Delta z_N$. Δz_l denotes the spacings of the mesh in the l th coordinate direction. The component $Q_{jk} = \int_{\Delta \mathbf{z}_j} q_{\mathbf{Z}}(\mathbf{z}, t_0 + \Delta t | \mathbf{z}_k, t_0) d\mathbf{z}$ of the transition probability matrix \mathbf{Q} signifies the probability of being in node j at the time $t = t_0 + \Delta t$ on condition of starting at the k th node at time $t = t_0$. Resuming this procedure a number n of times, the state \mathbf{p}_n is given as $\mathbf{p}_n = \mathbf{Q}^n \mathbf{p}_0$, attaining a stationary state as $n \rightarrow \infty$.

4. FRICTION CONTROLLED SLIP OF A STRUCTURE ON A FOUNDATION

The equation of motion for the slip displacement $S(t)$ of a structure on a foundation is

$$\ddot{S}(t) + \nu g \operatorname{sign}(\dot{S}) = -\ddot{G}(t) \quad (5)$$

where ν is the friction coefficient and $\ddot{G}(t)$ is the horizontal surface acceleration. In what follows, $\ddot{G}(t)$ is assumed to be white noise with intensity S_0 . Then, the exact stationary conditional pdf and the variance for the slip velocity conditioned on ν are

$$f_{\dot{S}}(\dot{s}|\nu) = \frac{\nu g}{2\pi S_0} \exp\left(-\frac{\nu g|\dot{s}|}{\pi S_0}\right), \quad \sigma_{\dot{S}}^2(\nu) = \frac{2\pi^2 S_0^2}{\nu^2 g^2} \quad (6)$$

ν is a random variable with pdf $f_\nu(\nu)$, mean $E[\nu]$ and coefficient of variation c_ν . The displacement $S(t)$ is not considered in the state vector as there is no stiffness term involved in this dynamic system. Then, the state vector consists of the velocity $\dot{S}(t)$ and the dummy random process $V(t) = \nu$. This yields $\mathbf{Z}(t)^T = [\dot{S}(t), V(t)]$, thus $N = 1 + 1 = 2$.

5. APPROXIMATING TRANSITIONAL PROBABILITY MATRIX

During a transition from the state $\mathbf{z}_k = (\dot{S}_k, \nu_k)$ at the time t_0 , the system is assumed to behave locally Gaussian assuming Δt to be small. The conditional mean value function $\boldsymbol{\mu}(t + \Delta t)$ and conditional covariance matrix $\boldsymbol{\kappa}(t_0 + \Delta t)$ are determined from the differential equations, Köylüoğlu et al. (1995.a).

$$\dot{\boldsymbol{\mu}}(t) = E[\mathbf{a}(\mathbf{Z}(t))] \quad , \quad \boldsymbol{\mu}(0) = \mathbf{z}_k \quad (7)$$

$$\dot{\boldsymbol{\kappa}}(t) = E\left[\frac{\partial}{\partial \mathbf{z}} \mathbf{a}(\mathbf{Z}(t))\right] \boldsymbol{\kappa}(t) + \boldsymbol{\kappa}(t) E\left[\frac{\partial}{\partial \mathbf{z}} \mathbf{a}(\mathbf{Z}(t))\right]^T + \mathbf{b}(t)\mathbf{b}^T(t) \quad , \quad \boldsymbol{\kappa}(0) = \mathbf{0} \quad (8)$$

(7) and (8) provide the solutions $E[\nu|\mathbf{z}_k] = \nu_k$ and $\kappa_{\dot{S}\nu} = \kappa_{\nu\nu} = 0$, so $q_{\mathbf{Z}}(\dot{s}, \nu, t_0 + \Delta t|\mathbf{z}_k, t_0) = \delta(\nu - \nu_k)\varphi((\dot{s} - \dot{\mu}_{\dot{S}})/\sqrt{\kappa_{\dot{S}\dot{S}}})/\sqrt{\kappa_{\dot{S}\dot{S}}}$, i.e. diffusion only takes place in the \dot{S} direction. $\mu_{\dot{S}}$ and $\kappa_{\dot{S}\dot{S}}$ are obtained by numerical integration of (9) and (10) over the interval $[0, \Delta t]$.

$$\frac{d}{dt}\mu_{\dot{S}}(t) = -\nu_k g \left(1 - 2\Phi\left(\frac{-\mu_{\dot{S}}(t)}{\sqrt{\kappa_{\dot{S}\dot{S}}(t)}}\right)\right) \quad , \quad \mu_{\dot{S}}(0) = \dot{S}_k \quad (9)$$

$$\frac{d}{dt}\kappa_{\dot{S}\dot{S}}(t) = -4\nu_k g \sqrt{\kappa_{\dot{S}\dot{S}}(t)} \varphi\left(\frac{\dot{\mu}_{\dot{S}}}{\sqrt{\kappa_{\dot{S}\dot{S}}(t)}}\right) + 2\pi S_0 \quad , \quad \kappa_{\dot{S}\dot{S}}(0) = 0 \quad (10)$$

6. NUMERICAL EXAMPLE

In the numerical example, the conditional variance of the slip velocity conditioned on the mean friction coefficient $\sigma_{\dot{S}}^2(E[\nu])$ is set to 1, i.e., $\frac{2\pi^2 S_0^2}{E[\nu]^2 g^2} = 1$. ν is assumed to be uniformly distributed in the interval $[E[\nu](1 - \sqrt{3})c_\nu, E[\nu](1 + \sqrt{3})c_\nu]$ where $E[\nu] = 0.5$ and c_ν denotes the coefficient of variation, which will be varied. Path integration results are obtained for the unconditional pdf $f_{\dot{S}}(s)$ of \dot{S} using a mesh with 40×40 cells, extending $\pm 4\sigma_{\dot{S}}$ in the \dot{S} direction and covering the ν direction. The transition time interval is selected as $\Delta t = 0.01 \frac{\pi S_0}{E[\nu]g}$. Numerical results shown with full line are compared in Figures 1 and 2 with the exact ones shown with dashed signature obtained by evaluating the compound probabilities analytically as given in eq. (11). As seen, $\sigma_{\dot{S}}$ in (11) is very different than (6). These are equal if $v_c \rightarrow 0$.

$$f_{\dot{S}}(\dot{s}) = \int_{\nu} f_{\dot{S}}(\dot{s}|\nu) f_{\nu}(\nu) d\nu \quad , \quad \sigma_{\dot{S}}^2 = \int_{\nu} \frac{2\pi^2 S_0^2}{\nu^2 g^2} f_{\nu}(\nu) d\nu = \frac{1}{1 - 3c_\nu^2} \frac{2\pi^2 S_0^2}{E[\nu]^2 g^2} \quad (11)$$




Figure 1: $f_{\dot{S}}(s)$, $c_\nu = 0.1$.




Figure 2: $f_{\dot{s}}(s)$, $c_{\nu} = 0.3$.

7. REFERENCES

1. Köylüoğlu, H.U., Nielsen, S.R.K. and Çakmak, A.Ş. (1995.a) *Fast Cell-to-Cell Mapping (Path Integration) with Probability Tails for the Stochastic Response of Nonlinear White Noise and Poisson Driven Systems*. Structural Safety, **17**, pp. 151-165.
2. Köylüoğlu, H.U., Nielsen, S.R.K. and Çakmak, A.Ş. (1995.b) *Solution of Random Structural System subject to Nonstationary Excitation: Transforming the Equation with Random Coefficients to one with Deterministic Coefficients and Random Initial Conditions*. Soil Dynamics and Earthquake Engineering, **14**, pp. 219-228.
3. Naess, A. and Johnsen, J.M. (1991), *Response Statistics of Nonlinear Dynamic Systems by Path Integration*. Proc. IUTAM Symposium on Nonlinear Stochastic Mechanics (Bellomo and Casciati, eds.), Torino, Italy, July, 1991, Springer-Verlag.
4. Sun, J.Q. and Hsu, C.S. (1990) *The Generalized Cell Mapping Method in Nonlinear Random Vibration based upon Short-Time Gaussian Approximations*, J. Appl. Mech., **57**, 1018-1025.

STRUCTURAL RELIABILITY THEORY SERIES

PAPER NO. 125: H. I. Hansen, P. H. Kirkegaard & S. R. K. Nielsen: *Modelling of Deteriorating RC-Structures under Stochastic Dynamic Loading by Neural Networks*. ISSN 0902-7513 R9409.

PAPER NO. 126: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Reliability Approximations for MDOF Structures with Random Properties subject to Random Dynamic Excitation in Modal Subspaces*. ISSN 0902-7513 R9440.

PAPER NO. 127: H. U. Köylüoğlu, S. R. K. Nielsen and A. Ş. Çakmak: *A Faster Simulation Method for the Stochastic Response of Hysteretic Structures subject to Earthquakes*. ISSN 0902-7513 R9523.

PAPER NO. 128: H. U. Köylüoğlu, S. R. K. Nielsen, A. Ş. Çakmak & P. H. Kirkegaard: *Prediction of Global and Localized Damage and Future Reliability for RC Structures subject to Earthquakes*. ISSN 0902-7513 R9426.

PAPER NO. 129: C. Pedersen & P. Thoft-Christensen: *Interactive Structural Optimization with Quasi-Newton Algorithms*. ISSN 0902-7513 R9436.

PAPER NO. 130: I. Enevoldsen & J. D. Sørensen: *Decomposition Techniques and Effective Algorithms in Reliability-Based Optimization*. ISSN 0902-7513 R9412.

PAPER NO. 131: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Approximate Forward Difference Equations for the Lower Order Non-Stationary Statistics of Geometrically Non-Linear Systems subject to Random Excitation*. ISSN 0902-7513 R9422.

PAPER NO. 132: I. B. Kroon: *Decision Theory applied to Structural Engineering Problems*. Ph.D.-Thesis. ISSN 0902-7513 R9421.

PAPER NO. 133: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Stochastic Dynamics of Nonlinear Structures with Random Properties subject to Random Stationary Excitation*. ISSN 0902-7513 R9520.

PAPER NO. 134: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Solution of Random Structural System subject to Non-Stationary Excitation: Transforming the Equation with Random Coefficients to One with Deterministic Coefficients and Random Initial Conditions*. ISSN 0902-7513 R9429.

PAPER NO. 135: S. Engelund, J. D. Sørensen & S. Krenk: *Estimation of the Time to Initiation of Corrosion in Existing Uncracked Concrete Structures*. ISSN 0902-7513 R9438.

PAPER NO. 136: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Solution Methods for Structures with Random Properties subject to Random Excitation*. ISSN 0902-7513 R9444.

PAPER NO. 137: J. D. Sørensen, M. H. Faber & I. B. Kroon: *Optimal Reliability-Based Planning of Experiments for POD Curves*. ISSN 0902-7513 R9455.

PAPER NO. 138: S.R.K. Nielsen & P.S. Skjærbæk, H.U. Köylüoğlu & A.Ş. Çakmak: *Prediction of Global Damage and Reliability based upon Sequential Identification and Updating of RC Structures subject to Earthquakes*. ISSN 0902-7513 R9505.

STRUCTURAL RELIABILITY THEORY SERIES

PAPER NO. 139: R. Iwankiewicz, S. R. K. Nielsen & P. S. Skjærbæk: *Sensitivity of Reliability Estimates in Partially Damaged RC Structures subject to Earthquakes, using Reduced Hysteretic Models*. ISSN 0902-7513 R9507.

PAPER NO 141: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Uncertain Buckling Load and Reliability of Columns with Uncertain Properties*. ISSN 0902-7513 R9524.

PAPER NO. 142: S. R. K. Nielsen & R. Iwankiewicz: *Response of Non-Linear Systems to Renewal Impulses by Path Integration*. ISSN 0902-7513 R9512.

PAPER NO. 145: H. U. Köylüoğlu, S. R. K. Nielsen, Jamison Abbott and A. Ş. Çakmak: *Local and Modal Damage Indicators for Reinforced Concrete Shear Frames subject to Earthquakes*. ISSN 0902-7513 R9521

PAPER NO. 146: P. H. Kirkegaard, S. R. K. Nielsen, R. C. Micaletti and A. Ş. Çakmak: *Identification of a Maximum Softening Damage Indicator of RC-Structures using Time-Frequency Techniques*. ISSN 0902-7513 R9522.

PAPER NO. 147: R. C. Micaletti, A. Ş. Çakmak, S. R. K. Nielsen & P. H. Kirkegaard: *Construction of Time-Dependent Spectra using Wavelet Analysis for Determination of Global Damage*. ISSN 0902-7513 R9517.

PAPER NO. 148: H. U. Köylüoğlu, S. R. K. Nielsen & A. Ş. Çakmak: *Hysteretic MDOF Model to Quantify Damage for TC Shear Frames subject to Earthquakes*. ISSN 1395-7953 R9601.

PAPER NO. 149: P. S. Skjærbæk, S. R. K. Nielsen & A. Ş. Çakmak: *Damage Location of Severely Damaged RC-Structures based on Measured Eigenperiods from a Single Response*. ISSN 0902-7513 R9518.

PAPER NO. 150: S. R. K. Nielsen & H. U. Köylüoğlu: *Path Integration applied to Structural Systems with Uncertain Properties*. ISSN 1395-7953 R9602.

PAPER NO. 151: H. U. Köylüoğlu & S. R. K. Nielsen: *System Dynamics and Modified Cumulant Neglect Closure Schemes*. ISSN 1395-7953 R9603.

PAPER NO. 154: J. D. Sørensen, M. H. Faber, I. B. Kroon: *Optimal Reliability-Based Planning of Experiments for POD Curves*. ISSN 1395-7953 R9542.

PAPER NO. 155: J. D. Sørensen, S. Engelund: *Stochastic Finite Elements in Reliability-Based Structural Optimization*. ISSN 1395-7953 R9543.

PAPER NO. 161: S. Engelund, J. D. Sørensen: *Stochastic Models for Chloride-initiated Corrosion in Reinforced Concrete*. ISSN 1395-7953 R9608.

Department of Building Technology and Structural Engineering
Aalborg University, Sohngaardsholmsvej 57, DK 9000 Aalborg
Telephone: +45 98 15 85 22 Telefax: +45 98 14 82 43