Aalborg Universitet



Field Test of Surfactant and Acoustic Vibration as Enhancement Methods for In Situ Alkaline Hydrolysis of Organophosphorus Pesticide DNAPL

MacKinnon, Leah; Durant, Neal; Petrovskis, Erik; Rügge, Kirsten; Nissen, Lars; Jørgensen, Torben Højbjerg; Bennedsen, Lars Rønn; Muff, Jens; Pennell, Kurt; Bondgaard, Morten

Published in:

in: H.V. Rectanus and S.H. Rosansky (Chairs). Remediation of Chlorinated and Recalcitrant Compounds-2014. Ninth International Conference on Remediation of Chlorinated and Recalcitrant Compounds (Monterey, CA; May 2014). www.battelle.org/chlorcon.

Publication date: 2014

Document Version Early version, also known as pre-print

Link to publication from Aalborg University

Citation for published version (APA):

MacKinnon, L., Durant, N., Petrovskis, E., Rügge, K., Nissen, L., Jørgensen, T. H., Bennedsen, L. R., Muff, J., Pennell, K., & Bondgaard, M. (2014). Field Test of Surfactant and Acoustic Vibration as Enhancement Methods for In Situ Alkaline Hydrolysis of Organophosphorus Pesticide DNAPL. In in: H.V. Rectanus and S.H. Rosansky (Chairs). Remediation of Chlorinated and Recalcitrant Compounds-2014. Ninth International Conference on Remediation of Chlorinated and Recalcitrant Compounds (Monterey, CA; May 2014). www.battelle.org/chlorcon. (pp. H-046). Batelle Memorial Institute.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
 You may not further distribute the material or use it for any profit-making activity or commercial gain
 You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from vbn.aau.dk on: February 08, 2025

Field Test of Surfactant and Acoustic Vibration as Enhancement Methods for In Situ Alkaline Hydrolysis of Organophosphorus Pesticide DNAPL

Leah MacKinnon (lmackinnon@geosyntec.com), Neal Durant, and Erik Petrovskis (Geosyntec Consultants, MD, USA) Kirsten Rügge, Lars Nissen, and Torben H. Jørgensen (COWI, Lyngby, Denmark) Lars R. Bennedsen (Rambøll, Denmark) Jens Muff (Aalborg University, Aalborg, Denmark) Kurt Pennell (Tufts University, MA, USA) Morten Bondgaard (Region Midtjylland, Denmark)

Background/Objectives. Groyne 42 is a former organophosphorus pesticide manufacturing waste disposal site located on the west coast of Denmark. The Site covers an area of 20,000 m². Chemical wastes were disposed of at the Site from 1953 to 1962 between two sand dunes situated close to the North Sea. The organophosphorous pesticides and associated contaminants are present as dense nonaqueous-phase liquids (DNAPLs) in certain portions of the Site. Residual DNAPL is widespread in hot spots, but little contaminant mass exists as a mobile separate phase. The estimated total mass of organophosphorous pesticides present (DNAPL + sorbed phase) is between 200 to 300 tons. A European Commission-funded demonstration project (www.northpestclean.dk) was initiated in September 2010 with the objectives of (1) determining the efficiency of using in situ alkaline hydrolysis (ISAH) for treating the organophosphorus pesticide DNAPL, and (2) testing, in side-by-side field experiments, various techniques to enhance in situ delivery and contact between the reagent (caustic soda) and the contaminants. Surfactant flushing was one of the three enhancement methods to be tested.

Approach. Laboratory studies were completed to identify surfactants capable of enhancing the solubility of the pesticides under strongly alkaline (pH 12) conditions. Alcohol ethoxylates were found to be the most effective and were selected for the field experiments. The field demonstration project is being performed in three (10 m wide x 10 m long x 15 m deep) test cells. The test cells have been constructed using iron sheet piles to maximize hydraulic control. During the first stage of the project, ISAH was tested without enhancement (i.e., under static conditions) over a period of 8 months. In the second stage of treatment, recirculation was used in combination with ISAH in one of these test cells over a period of 12 months to evaluate any enhancement in reactivity due to mixing. In the final treatment stage, an alcohol ethoxylate surfactant was injected into the test cell at a target in situ concentration of 3% (wt.), for a final 8 month treatment period. Measurements of surface tension were used to evaluate the distribution of surfactant solution within the test cell. During each treatment stage, groundwater samples were collected to evaluate the progress of hydrolysis. Groundwater and soil sample analytical results were used to evaluate changes in the mass and distribution of pesticides through the three stages. The final stage of the pilot test will be complete in November 2013.

Results. The recirculation and surfactant flushing stages of the demonstration project were found to promote mixing of the pesticides and caustic soda in the test cell. Surface tension and contaminant measurements confirmed that the surfactant effectively increased the solubility of the pesticides to enhance the ISAH treatment. The results from the three stages of the demonstration project will be discussed in terms of the relative benefits and practical considerations for ISAH during static, recirculation and surfactant flushing conditions.



Field Test of Surfactant and Acoustic Vibration as Enhancement Methods for ISAH of Organophosphorus Pesticide DNAPL

L. MacKinnon, K. Rügge, L.R. Bennedsen, T.H. Jørgensen, N. Durant, M. Thomas, R. Bachus and M. Bondgaard



Creative Thinking Valued Solutions



Posters:

C5 – Tuesday - Comparison of Contaminated Mass Estimation Methods in a Large Field-Scale Experiments with In Situ Alkaline Hydrolysis.

H5 – Wednesday - In Situ Alkaline Hydrolysis (ISAH) of Insecticides—A Large-Scale Demonstration Project.

H5 – Wednesday - Selection and Testing of Surfactants for Enhanced In Situ Alkaline Hydrolysis (S-ISAH) of Pesticide DNAPL.





Outline

- The Høfde Site and COCs
- ISAH Technology
- Pilot Test Objectives and Program
- Approach and Results:
 - ISAH with no enhancement
 - ISAH with acoustic vibration
 - ISAH with recirculation
 - ISAH with surfactant
- Conclusions





Site Layout & OPPs





- ISAH products less toxic and more water soluble than parents
- Technology used at Cheminova site for wastewater treatment in sequence with a biolagoon



Parathion (EP3) \rightarrow Diester phosphoric + p-nitrophenol (PNF)acid (EP2 acid)





- To demonstrate in a large-scale pilot experiment the efficiency of a novel remediation method that uses ISAH to treat organophosphorous pesticide (OPP) contaminated soil and groundwater
- To demonstrate, in side-by-side pilot experiments, the performance and usability of different "enhancement" technologies
 - 1. Groundwater Recirculation
 - 2. Surfactants
 - 3. Acoustic Vibration





Test Cell Layouts







Pilot Test Program

	2011									20							12						201					13				
	Μ	Α	M	1 J	J	A	5	5 C) N	D	J	F	Μ	Α	Μ	J	J	Α	S	0	Ν	D	J	F	Μ	Α	Μ	J	J	A	S (N C
	Initial characterization					۱	С			Суо	Cycle 1					Сус						:le 2					Cycle 3					
Operation																																
Draining and NaOH infiltration																																
TC 1 - Vibrations																																
TC 2 - Recirculation																																
TC 2 - Surfactant																																
TC 3 - ISAH - no enhancement																																
Monitoring																																
Soil sampling																																
Water sampling																																

- 3 "Cycles" of operation between 2011 and 2013
- Lines of evidence for ISAH:
 - Groundwater → Changes in OPPs + hydrolysis products
 - Soil → Changes in OPPs





Cycle 1 Implementation: NaOH Injection

- Test cells drained in advance of NaOH Injection
- NaOH added at pH >12
- Monitoring for 8 months





Cycle 1 Monitoring Results







- PNF & EP2 produced
- Plateau after a few months
 - pH decrease
 - Daughter products degrade over time







Cycle 2: ISAH with Vibration







10 meter width (test cell is 100 m2)

10 meter width (test cell is 100 m2)

Stationary Vibration Device









Propagation of Vibration



Creative Thinking

Valued Solutions





Vibration Results



ISAH lasted longer & at faster rates compared to Cycle 1
 → mixing caused by vibration
 → pH stayed in target range

Creative Thinking Valued Solutions



Cycle 2: Recirculation









Recirculation Results





- NaOH, COC
 concentrations mix
 between depths
- > pH decreases below target range







Cycle 3: Surfactant



















Mass estimates for EP3 in the ATA



Creative Thinking Valued Solutions



- Between 198 and 497 kg OPPs, (41% to 68%) of the estimated initial mass were removed over the three cycles by ISAH.
- Slower mass removal in later cycles, as most reactive OPPs and initial dissolved phase mass removed.
 →Mass transfer limitations.







Vibration

 The vibration technology delivered vibration to the target depth & hydrolysis rates were enhanced over ISAH without enhancement.

Recirculation

- Recirculation provided mixing of NaOH and OPPs
- Rates limited due to pH less than target range

Recirculation and Surfactant

- Surfactant addition increased the dissolved concentration of the OPPs and reduced mass on soil
- Rates increase when pH increased to target range





Questions?

