

On the Performance of One Stage Massive Random Access Protocols in 5G Systems

Mahmood, Nurul Huda; Pratas, Nuno; Jacobsen, Thomas; Mogensen, Preben Elgaard

Published in:

Turbo Codes and Iterative Information Processing (ISTC), 2016 9th International Symposium on

DOI (link to publication from Publisher):

[10.1109/ISTC.2016.7593133](https://doi.org/10.1109/ISTC.2016.7593133)

Creative Commons License

Unspecified

Publication date:

2016

Document Version

Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Mahmood, N. H., Pratas, N., Jacobsen, T., & Mogensen, P. E. (2016). On the Performance of One Stage Massive Random Access Protocols in 5G Systems. In *Turbo Codes and Iterative Information Processing (ISTC), 2016 9th International Symposium on* (pp. 340-344). IEEE (Institute of Electrical and Electronics Engineers). <https://doi.org/10.1109/ISTC.2016.7593133>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

On the Performance of One Stage Massive Random Access Protocols in 5G Systems

Nurul H. Mahmood¹, Nuno Pratas¹, Thomas Jacobsen¹ and Preben Mogensen^{1,2}

¹Department of Electronic Systems, Aalborg University, Denmark.

²Nokia Bell Labs, Aalborg, Denmark.

{nhm, nup, tj, pm}@es.aau.dk

Abstract—The next generation of cellular systems are expected to experience a proliferation of the number of emerging use cases alongside supporting high speed mobile broadband services. Massive Machine Type Communication (mMTC), which caters to a large number of low-data rate and low-cost devices, is such an use case. Smart utility meters, automated sensors in farms, and vehicle tracking nodes for logistics monitoring are all examples of emerging mMTC devices. Ensuring efficient mechanisms to access the wireless channel for such a massive number of densely deployed devices is the key challenge posed by mMTC applications. A framework for the analysis of the *one-stage* massive access protocol is proposed in this paper, which allows to model and evaluate its performance with respect to important performance metrics for mMTC services.

Index Terms—Massive random access, M2M, mMTC, IoT, 5G, one-stage RA.

I. INTRODUCTION

The fifth generation wireless systems (5G) is expected to experience a proliferation in the number of emerging use cases categorized into several broad service groups such as: enhanced Mobile Broadband (eMBB) supporting an evolution of today's broadband traffic with an increased spectral efficiency, Ultra-Reliable Low Latency Communications (URLLC) where messages need to be transferred with high reliability and low latency, and massive Machine Type Communication (mMTC) catering to a large number of (generally) low-data rate, low-cost devices [1].

One of the main drivers behind mMTC services is the role of Machine Type Devices (MTD) as an enabler for the Internet of Things (IoT). Massive machine type communications are commonly characterized by a large number of MTDs associated with each base station [2], the possibility of asynchronous activation of a massive number of MTDs [3], low payload sizes and traffic asymmetry in which the uplink traffic dominates the downlink [4].

The random access (RA) procedure in Long Term Evolution (LTE) is not suitable for mMTC services due to the associated signaling overhead [5]–[8]. Namely, the LTE access procedure is composed of a contention stage (where the devices contend for access) and a non-contention stage (where the scheduling and the transmission of the uplink payload occurs). However, for small data payloads, the additional signalling overhead incurred by the non-contention stage is extremely sub-optimal in an mMTC context [8].

One-stage access protocols are now being considered as a low signaling overhead alternative for the random access with mMTC services. These types of cellular RA schemes has been put forward first in [9], and has formed

the basis of various other similar access protocols [10]–[12]. Specifically, one-stage access denotes the case where the devices contend (i.e., perform random access) directly with their uplink payload. Upon the MTD transmission of the preamble (along with the data), the eNodeB (eNB) acknowledges the reception via an ACK/NACK message. The access itself is performed over a time and frequency resource assigned for RA. Since the access is uncoordinated, it is possible that multiple MTDs will attempt to access the same network resource, resulting in a collision. In case the eNB is not able to decode the collided transmissions, each affected MTD will re-attempt access at a later random access resource.

Ideally, *one-stage* access protocols should be the preferred access mechanisms for mMTC services due to its low overhead. However, their applicability depends on two main factors: (1) the data payload size, and (2) the device density. Specifically, as the data payload increases the number of required network resources increases proportionally. When collisions occur and the base station is not able to decode the transmitted information, then these resources are wasted. Therefore, for a high number of active MTDs and higher payloads, the access scheme in place in LTE could be preferable. However, for a low number of active MTDs, fewer collisions will occur making the one-stage access protocol desirable.

In this paper our goal is to provide insights for the design of RA protocols for mMTC services in a 5G setting. Specifically, we model the performance of the one-stage access protocol using stochastic geometry tools [13]. To cover the wide variation in the kinds of devices, MTDs capable of adjusting their transmission power to compensate for the path loss are considered alongside simple low-cost fixed transmit power devices. The findings from this contribution will help to identify the network conditions from a physical layer perspective under which the *one-stage* access protocol can sufficiently meet a desired service target.

The rest of the paper is structured as follows: Section II details the system model and assumptions, the signal and the collision model, and the evaluated performance metrics. The analytical expressions for the considered performance metrics are derived in Section III. Section IV provides numerical and simulation results, and discussions. Concluding remarks are found in Section V.

II. SYSTEM MODEL

We consider a single cell of radius R in a multi-cell network. The eNB is located at the cell center, with uniformly distributed MTDs throughout the cells as shown in Figure 1. The number and the location of the MTDs are modelled according to an independent homogeneous PPP Φ_u with intensity $\lambda_u = \pi R^2 \tilde{\lambda}_u$, where $\tilde{\lambda}_u$ is the device density per square meter. Specifically, for a given PPP, the number of points and their locations are random and respectively follow a Poisson and an uniform distributions [13]. We assume that a device randomly chooses to transmit with probability ρ ($\rho \leq 1$) at each RA opportunity.

Once a device decides to transmit, it will randomly choose a RA preamble, i.e. a digital signature that the MTD transmits. These preambles are used by the eNB to estimate the channel, and simultaneously decode the MTDs transmitted payload. We assume that there are M orthogonal pseudo-random RA preambles available for the transmitting MTDs to choose from. Information about the available RA preambles is periodically broadcast by the eNB.

Transmission with probability ρ results in independent thinning of the PPP Φ_u . Hence, the number of devices transmitting concurrently is again a PPP Φ_t of lower density $\lambda_t = \lambda_u \rho$ [13]. Due to the orthogonal nature of the RA request preambles, a transmitting device only experiences interference from other concurrently transmitting devices using the same preamble. As a result, the number of interfering devices is again a PPP Φ with intensity $\lambda = \frac{\lambda_t}{M}$, resulting from the thinning of Φ_t .




Fig. 1: System Model showing the random distribution of the MTDs with the cell divided into multiple rings.

A. Signal Model

The transmission of a random device located at a distance d meters away from the eNB is analysed in this contribution. The desired signal of interest can be given as $S = P_T d^{-\alpha} g_d$, where P_T is the transmit power, α is the path loss exponent and g_d is the random channel fading power. The desired device experiences interference from all other concurrently transmitting devices that uses the same preamble, which form the PPP Φ . Thus, the sum interference I_s can be expressed as:

$$I_s = \sum_{x \in \Phi} P_T r_x^{-\alpha} g_x, \quad (1)$$

where r_x and g_x are the random distance and the channel fading power of the devices to the eNB. Since Φ is a stationary PPP, the PDF of the distance r_x is given by the Rayleigh

distribution, i.e., $f_{r_s}(r) = 2\pi\lambda r \exp(-\pi\lambda r^2)$ [13], defined for $r \geq 1$. Note that, we explicitly assume $r \geq 1$ to avoid amplification of the signal for $0 < r < 1$, and the singularity at $r = 0$.

B. Collision Model

To cover the wide range of MTD types, we consider two different approaches to determine whether a RA request is successful, namely the *singleton* approach and the *SINR* approach, as detailed below.

1) *Singleton Approach*: Whenever an MTD accesses the channel, it selects one of the M available preambles. A collision is said to occur if two or more devices transmit the same RA request preamble on the same RA opportunity. Different RA request preambles can be detected by the eNB thanks to their orthogonality. However, a collision is not detected by the eNB if the two devices transmitting the same preamble are equidistant from the eNB, resulting in a false ACK. We use the term *blocking probability* to denote this scenario. In the event of a collision, the MTDs will reattempt access after a random backoff time. The backoff period consists of a fixed backoff time of b_1 RA opportunities, followed by a random backoff time uniformly distributed in $[0, b_2]$ slots.

2) *SINR Approach*: Decaying of the signal power with distance is a fundamental feature of the wireless channel. The effects of channel propagation can be overcome with channel inversion power control, i.e., by transmitting with power $P_T = d^\alpha$, such that all transmissions are received with the same average received power at the eNB. However, this does not account for the power variation due to shadowing and fading. Furthermore, channel inversion may not always be possible due to the maximum transmit power constraints limiting P_T to be below a certain level; and for very simple and low-cost MTDs without this capability.

An alternative approach for the success probability evaluation is through the analysis of the random signal-to-interference plus noise ratio (SINR). In this approach, all devices are assumed to transmit with a constant power P_T . A RA transmission can be considered successful if the SINR exceeds a given threshold γ_{th} . The SINR for the desired device's signal at the eNB, γ_s , is given by $\gamma_s = \frac{S}{I_s + N_0}$, where I_s is the sum interference from other devices as given by Eq. (1), and N_0 is the thermal noise power.

C. Performance Evaluation Metrics

The performance of the one-stage access protocol is evaluated in this contribution considering the following evaluation metrics.

1) *Channel Occupancy Rate*: The channel occupancy rate, p_{ch} , is a general network evaluation criteria indicating the number of RA opportunities resulting in successful transmission. This is related to the singleton approach, and is given as the probability that there is exactly one active node in the PPP Φ . Specifically, $p_{ch} = \mathbb{P}[N = 1]$, where the Poisson distributed random number N is the cardinality of the PPP Φ .

2) *Blocking Probability*: To determine the blocking probability, we divide the cell into K equi-radius circular rings as shown in Figure 1. The radius of each ring is chosen such that all nodes within the same ring arrive at the eNB with negligible time difference. The blocking probability is then given by the probability of having two or more devices attempting to simultaneously access the channel using the same preamble from the same ring.

Let \mathcal{R}_k denote the k^{th} ring. The active MTDs in \mathcal{R}_k choosing the same RA preamble then forms a PPP Φ_k with density $\lambda_k = \frac{\lambda\pi((Rk/K)^2 - (R(k-1)/K)^2)}{\pi R^2} = \frac{\lambda(2k-1)}{K^2}$. The blocking probability for MTDs in the k^{th} ring is therefore given by $p_{block,k} = \mathbb{P}[N_k \geq 2]$, where N_k is the random number of nodes in the PPP Φ_k .

3) *Success Probability*: With the singleton approach, the random number of concurrently transmitting MTDs (irrespective of the selected RA preamble) is N_t , which is in fact the cardinality of the PPP Φ_t . A transmission attempt is said to be successful when the randomly selected RA preamble of an MTD attempting to transmit does not overlap with that of the other $N_t - 1$ co-transmitting MTDs. Mathematically, this can be expressed as $p_{single} = \mathbb{P}[N = 1 | N_t \geq 1]$.

On the other hand, the success probability for the SINR approach for a given target SINR γ_{th} is given as $p_{SINR} = \mathbb{P}[\gamma_s \geq \gamma_{th}]$, where γ_s is the desired SINR.

III. PERFORMANCE ANALYSIS FRAMEWORK

The performance metrics of interest, as introduced in Section II-C are derived analytically in this section.

A. Channel Occupancy Rate and Blocking Probability

Owing to the PPP model assumption, the channel occupancy rate and the blocking probability are derived from the Poisson distribution as

$$p_{ch} = \lambda e^{-\lambda} \quad \text{and} \quad p_{bl,k} = 1 - e^{-\lambda} - \lambda_k e^{-\lambda}, \quad (2)$$

where $\lambda = \frac{\lambda_u \rho}{M}$ is the density of the random PPP Φ , with λ_u being the number of contending MTDs; and $\lambda_k = \frac{\lambda(2k-1)}{K^2}$.

B. Success Probability

1) *Singleton Approach*: The success probability with the singleton approach is given by $p_{single} = \mathbb{P}[N = 1 | N_t \geq 1]$. Using Baye's rule, p_{single} can be expressed as $p_{single} = \mathbb{P}[N = 1, N_t \geq 1] / \mathbb{P}[N_t \geq 1]$. We can evaluate $\mathbb{P}[N = 1, N_t \geq 1]$ by conditioning on N_t , followed by taking the expectation over its distribution; i.e., $\mathbb{P}[N = 1, N_t \geq 1] = \mathbb{E}_{N_t \geq 1}[\mathbb{P}[N = 1 | N_t]]$, where $\mathbb{E}[\cdot]$ is the expectation operator.

Let us consider a transmitting MTD and $N_t - 1$ potential colliding MTDs. Since the RA preambles are chosen randomly with uniform probability, the probability $\mathbb{P}[N = 1 | N_t]$ is the probability that none of these $N_t - 1$ MTDs chooses the RA preambles selected by the desired MTD. Hence, $\mathbb{P}[N = 1 | N_t] = \left(\frac{M-1}{M}\right)^{N_t-1}$. Following the Poisson distributed random variable N_t , the expectation over $\mathbb{P}[N = 1 | N_t]$ evaluates to

$$\mathbb{E}_{N_t \geq 1}[\mathbb{P}[N = 1 | N_t]] = \sum_{n \geq 1} \left(1 - \frac{1}{M}\right)^{n-1} \frac{\lambda_t^n e^{-\lambda_t}}{n!}.$$

After some algebraic manipulations, the singleton success probability can be succinctly expressed as

$$p_{single} = \frac{\exp(-\lambda) - \exp(-\lambda_t)}{\left(1 - \frac{1}{M}\right)(1 - \exp(-\lambda_t))}, \quad (3)$$

where $\lambda_t = \lambda_u \rho$ is the density of the PPP Φ_t .

2) *SINR Approach*: Using the definition of the SINR γ_s , the success probability for the SINR approach p_{SINR} can be re-expressed as $p_{SINR} = \mathbb{P}[\gamma_s \geq \gamma_{th}] = \mathbb{P}[S - \gamma_{th} I_s \geq \gamma_{th} N_0]$. Let us define the random variable $u \triangleq S - \gamma_{th} I_s$. Hence, p_{SINR} can be written as $p_{SINR} = \mathbb{P}[u \geq \gamma_{th} N_0] = 1 - F_u(\gamma_{th} N_0)$, where $F_u(\cdot)$ is the cumulative density function (CDF) of u .

Evaluating the CDF of u directly requires an expression for the probability distribution function (PDF) of I_s , which is not readily obtainable. We propose to circumvent this limitation by using the relationship between the CDF and the Laplace Transform (LT), which leads to the SINR success probability being derived as [14, Eq. 19]

$$p_{SINR} = 1 - \frac{1}{2\pi j} \oint \frac{\mathcal{M}_u(s)}{s} \exp(s\gamma_{th} N_0) ds, \quad (4)$$

where $\mathcal{M}_u(s)$ is the LT of u defined as $\mathcal{M}_u(s) = \mathbb{E}[\exp(-su)]$. By the independence assumption between desired signal S and the sum interference I_s , we readily obtain $\mathcal{M}_u(s) = \mathcal{M}_S(s) \mathcal{M}_{I_s}(-\gamma_{th} s)$, where $\mathcal{M}_S(s)$ and $\mathcal{M}_{I_s}(s)$ are the LTs of S and I_s respectively.

Assuming Rayleigh fading channels, the desired channel power gain S is exponentially distributed with mean $P_T d^{-\alpha}$. The corresponding Laplace Transform of S is then $\mathcal{M}_S(s) = (1 + sP_T d^{-\alpha})^{-1}$ [15]. On the other hand, the Laplace Transform of I_s is obtained as

$$\begin{aligned} \mathcal{M}_{I_s}(s) &= \mathbb{E}[\exp(-s I_s)] \\ &= \mathbb{E}_{\Phi, g_d} \left[\prod_{x \in \Phi} \exp(-s P_T r_x^{-\alpha} g_x) \right] \\ &= \mathbb{E}_{\Phi} \left[\prod_{x \in \Phi} (1 + s P_T r_x^{-\alpha})^{-1} \right] \\ &= \exp \left[-2\pi\lambda \int_1^\infty \left(1 - (1 + s P_T r_x^{-\alpha})^{-1}\right) r_x dr_x \right] \\ &= \exp \left(-\pi\lambda \left({}_2F_1 \left[1, \frac{-2}{\alpha}, 1 - \frac{2}{\alpha}, -s P_T \right] - 1 \right) \right). \end{aligned} \quad (5)$$

The first step in Eq. (5) follows from the independence assumption among the interference from the different sources; the second step is obtained by assuming a Rayleigh fading channel model (i.e., an exponentially distributed g_x); the third step is the result of invoking the probability generating functional of the PPP distribution [13]; and the final step is evaluated by carrying out the integration using the distribution of r as given in Section II-A.

IV. NUMERICAL RESULTS

We now present numerical results based on analytical expressions developed in Section III and investigate the impact of key system parameters on the performance. The simulations adopt the following parameters, unless stated otherwise: number of RA preambles $M = 50$, path loss

exponent $\alpha = 3$, target SINR of 0 dB and transmit power $P_T = 0$ dBm. The channel occupancy rate and blocking probability of the network, and transmission success probabilities for the singleton and SINR approaches are evaluated through MATLAB based Monte-Carlo simulations. The presented results provide insights into the operation of the *one-stage* access protocol and its limitations with respect to the network parameters.

A. Channel Occupancy Rate and Blocking Probability

The channel occupancy rate for different transmission probabilities ρ with number of contending MTDs $\lambda_u \approx [315, 630, 1600]$ is presented in Figure 2a; alongside the blocking probability for different transmission regions $k \in \{1 \dots K\}$ with $K = 3$ for $\lambda_u = 630$ MTDs in Figure 2b. Analytical findings presented in Section III are found to closely match the simulation results. We can observe that the maximum channel occupancy rate is around 37%, which is in-line with the well known occupancy figures of framed slotted ALOHA-like RA approaches. It is however interesting to note that a large number of transmissions results in false ACK (corresponding to the blocking probability) with high device density. This results from many devices at similar distances to the eNB having to choose the RA preamble from a fixed set. In fact, this is one of the inherent limitations of the *one-stage* random access procedure. Improved access mechanisms are required to overcome such high blocking probabilities.




Fig. 2: Simulated and Analytical Channel Occupancy Rate and Blocking Probability vs. transmission probability (ρ) with the singleton approach.

B. Success Probability - Singleton Approach

The success probability for an MTD attempting transmission with the singleton approach, as analysed in Section III-B, is illustrated in Figure 3. Contrary to the trends observed in Figure 2, it is always better for an MTD to transmit with a lower probability ρ . This is due to the success probability only accounting for the RA opportunities with transmission attempts, and hence idles slots are not accounted for. Therefore, a careful selection of the transmission probability ρ is an important step for the *one-stage* access mechanism, especially at massive MTD densities.

The cumulative success probability after the n^{th} retransmission attempt for $\rho = 0.1$ is shown in Figure 4. The average number of re-transmissions required to achieve a target success probability can be extracted from such cumulative success probability curves.




Fig. 3: Success Probabilities vs. transmission probability ρ with the singleton approach and $\lambda_u = [314, 628, 1570]$ users




Fig. 4: Cumumulative Success Probabilities after n^{th} re-attempt for $\rho = 0.1$ with the singleton approach and $\lambda_u = [314, 628, 1570]$ users.

C. Success Probability - SINR Approach

Complementary to the singleton approach, the success probabilities with the SINR approach for a target SINR $\gamma_{th} = 0$ dB for various transmission probabilities ρ and normalized device distance to the eNB with MTD density $\lambda_u = 500$ MTDs is presented in Figure 5. Since the same transmit power and the same transmission probability is considered for all devices, MTDs closer to the eNB experience a higher success probability compared to those at the cell edge in general.

Similar to the trends in Figure 3, the success rate falls with increasing transmission probability ρ . However, devices closer to the eNB are much less affected compared to those further away. In fact MTDs closer to the cell edge experiences a very low success rate as a result of the overwhelming interference with $\rho = 0.5$. To overcome this limitation, we investigated the impact of having a variable transmission probability in Figure 6. First we consider only a distance dependent transmission probability where $\rho \propto \frac{1}{d}$, i.e. the MTDs closer to the eNB transmit with a smaller probability compared to those further away. As a result, MTDs further away from the eNB are less likely to be swarmed with strong interference from MTDs closer to the eNB. Such a distance dependent dynamic ρ is found to provide a success probability improvement of approximately 25% over having a fixed ρ .

In addition, significantly further improvement to the success probability is observed when we incorporate the network information in selecting ρ . For example, allowing

$\rho \propto \frac{1}{d\lambda_u}$ results in more than 300% gain for cell edge MTDs, as shown in Figure 6. It must be noted that additional signalling or autonomous *neighbour awareness protocols* are required for MTDs to estimate the device density λ_u . Furthermore, the cost of such increased success probabilities is increased delays associated with having a lower ρ .




Fig. 5: Simulated and Analytical Success Rate vs. normalized distance to the eNB with the SINR approach for $\rho = [0.05, 0.2, 0.5]$ and $\lambda_u = 500$ MTDs.




Fig. 6: Success Rate vs. normalized user distance with a variable transmission probability for $\lambda_u = 1500$ MTDs.

Figure 6 summarily demonstrates the potential of incorporating location and network awareness into the random access protocol. However, detailed investigation into such awareness mechanisms is beyond the scope of this contribution, and is left for future studies.

V. CONCLUSION

The existing access procedure in 3GPP LTE needs to be revised to handle the massive Machine Type Communication services envisioned for 5G systems. The *one-stage* random access procedure is a simple proposal aimed at addressing the mMTC access challenge. This paper presents a generic evaluation of the *one-stage* RA mechanism. Two different approaches are considered, namely: the *singleton approach* - where the transmission from all the devices arrive at the eNB with the same average received power; and the *SINR approach* - wherein all devices are assumed to transmit with a constant power. Various performance indicators encompassing both, the network and the device perspective, are evaluated. All analytically derived findings are validated via extensive system level Monte-Carlo simulations.

The evaluation framework presented in this paper has shown its potential in evaluating the advantages and the limitations of the *one-stage* RA protocol for large scale machine type communication. Furthermore, the potential of incorporating location and network awareness into the random access protocol is summarily demonstrated. As part of the future work, we would like to investigate possible enhancements that can improve the channel occupancy rate from the current maximum of $\sim 37\%$, and perform a comparative analysis of the *one-stage* RA procedure with other RA proposals for massive random access.

ACKNOWLEDGEMENT

This work has been performed in the framework of the Horizon 2020 project FANTASTIC-5G (ICT-671660) receiving funds from the European Union. The authors would like to acknowledge the contributions of their colleagues in the project, although the views expressed in this contribution are those of the authors and do not necessarily represent the project.

REFERENCES

- [1] N. H. Mahmood *et al.*, "Radio resource management techniques for eMBB and mMTC services in 5G dense small cell scenarios," in *InProc. IEEE VTC-Fall*, Montreal, Canada, Sep. 2016, accepted.
- [2] M. T. Islam, A. e. M. Taha, and S. Akl, "A survey of access management techniques in machine type communications," *IEEE Communications Magazine*, vol. 52, no. 4, pp. 74–81, Apr. 2014.
- [3] G. C. Madueno *et al.*, "Assessment of LTE wireless access for monitoring of energy distribution in the smart grid," *IEEE JSAC*, vol. 34, no. 3, pp. 675–688, Mar. 2016.
- [4] M. Z. Shafiq *et al.*, "Large-scale measurement and characterization of cellular machine-to-machine traffic," *IEEE/ACM Transactions on Networking*, vol. 21, no. 6, pp. 1960–1973, Dec. 2013.
- [5] A. Biral *et al.*, "The challenges of M2M massive access in wireless cellular networks," *Digital Communications and Networks*, vol. 1, no. 1, pp. 1–19, 2015.
- [6] A. Zanella *et al.*, "M2M massive wireless access: Challenges, research issues, and ways forward," in *Globecom Workshops (GC Workshops)*, 2013 IEEE, Dec 2013, pp. 151–156.
- [7] G. Madueno, S. Stefanovic, and P. Popovski, "Efficient LTE access with collision resolution for massive M2M communications," in *Globecom Workshops (GC Workshops)*, 2014, Dec 2014, pp. 1433–1438.
- [8] A. Laya, L. Alonso, and J. Alonso-Zarate, "Is the random access channel of LTE and LTE-A suitable for M2M communications? A survey of alternatives," *Communications Surveys Tutorials, IEEE*, vol. 16, 2014.
- [9] C. Schlegel, R. Kemper, and P. Kota, "A novel random wireless packet multiple access method using CDMA," *IEEE Transactions on Wireless Communications*, vol. 5, no. 6, pp. 1362–1370, June 2006.
- [10] "Deliverable D4.2 - 5GNow final MAC/networking concepts," 5th Generation Non-orthogonal Waveform for Asynchronous Signalling (5GNow), Tech. Rep., 2015.
- [11] S. Saur, A. Weber, and G. Schreiber, "Radio access protocols and preamble design for machine type communications in 5G," in *Asilomar Conference on Signals, Systems, and Computers*, Nov 2015.
- [12] D. Lin, G. Charbit, and I.-K. Fu, "Uplink contention based multiple access for 5G cellular IoT," in *Vehicular Technology Conference (VTC Fall)*, 2015 IEEE 82nd, Sept 2015, pp. 1–5.
- [13] M. Haenggi and R. K. Ganti, "Interference in large wireless networks," *Foundations and Trends in Networking*, vol. 3, no. 2, pp. 127–248, Feb. 2009.
- [14] N. H. Mahmood, F. Yilmaz, M.-S. Alouini, and G. E. Øien, "Heterogeneous next-generation wireless network interference model and its applications," *Transactions on Emerging Telecommunications Technologies*, vol. 25, no. 5, pp. 563–575, May 2014.
- [15] M. K. Simon and M.-S. Alouini, *Digital Communication over Fading Channels*, 2nd ed. New Jersey, USA: John Wiley & Sons, Dec. 2005.