

Energy release in isothermally stretched silicate glass fibers

Hornbøll, Lasse; Lönnroth, Nadja Teresia; Yue, Yuanzheng

Publication date:
2005

Document Version
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):
Hornbøll, L., Lönnroth, N. T., & Yue, Y. (2005). *Energy release in isothermally stretched silicate glass fibers*. Abstract from The 106th American Ceramic Society Annual Meeting, Symposium on Inorganic Fibers, Baltimore, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Energy release in isothermally stretched silicate glass fibers

L. Hornbøll, N. Lönnroth and Y.-Z. Yue

Glass annealed near the glass transition temperature (T_g) shows no energy release behavior below T_g during reheating in a differential scanning calorimeter (DSC) at a heating rate (q_h) equal to prior cooling rate (q_c). However, when the glass is annealed near T_g and cooled under a mechanical force, an energy release peak occurs during DSC measurements at $q_h = q_c$. This behavior is similar to that of a hyperquenched glass, cooled at $q_c \gg q_h$. Here we show the energy release behavior of the isothermally stretched silicate fibers. The results suggest that the energy stored in glass fiber during spinning processes consists of two parts, i.e. the thermal quenching induced part and the mechanical stretching induced one. The latter part should be taken into account in calculating the average fictive temperature and the cooling rate of fibers, especially in the case of slowly drawn thick fibers. Until recently this part has been supposed to be insignificant in estimating the fictive temperature and the cooling rate of the hyperquenched fibers. The impact of annealing temperature, mechanical load, and composition on the mechanically induced energy release behavior are investigated by doing systematic experiments on glass fibers with different chemical compositions. The results show a clear dependence on both load and annealing temperature. The higher mechanical strength of fibers in comparison to that of a bulk glass of the same compositions could be attributed partly to the observed effect. Therefore, measurements on mechanical properties of the fibers have also been carried out, as well as calculations of the rheology based on the isothermal stretching experiments.