

ChromaBot - Prototyping Soft Robotic Actuators with Integrated Electrochromic Displays

Milthers, Anna Dagmar Bille; Löchtefeld, Markus

Published in:

20th International Conference on Mobile and Ubiquitous Multimedia

DOI (link to publication from Publisher):

[10.1145/3490632.3497831](https://doi.org/10.1145/3490632.3497831)

Publication date:

2021

Document Version

Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Milthers, A. D. B., & Löchtefeld, M. (2021). ChromaBot - Prototyping Soft Robotic Actuators with Integrated Electrochromic Displays. In *20th International Conference on Mobile and Ubiquitous Multimedia* (pp. 198-200). Association for Computing Machinery (ACM). <https://doi.org/10.1145/3490632.3497831>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

ChromaBot - Prototyping Soft Robotic Actuators with Integrated Electrochromic Displays

ANNA DAGMAR BILLE MILTHERS, Aalborg University, Denmark

MARKUS LÖCHTEFELD, Aalborg University, Denmark




Fig. 1. Examples of two different soft-robotic actuators with build in electrochromic displays produced with the ChromaBot method.

Soft robotics - robots built from highly compliant materials that resemble soft biological materials - have recently become more popular especially in industry settings, given their ability to handle fragile objects. One problem however of these devices is that they can only communicate intent or the need for help through movement. To overcome this limitation, in this paper we present ChromaBot, a method towards prototyping soft robotic actuators with integrated printed electrochromic displays. Our method only degrades the longevity of the soft robotic actuator in an acceptable manner while at the same time allows for a more expressive soft robot. We present detailed instructions on how to prototype ChromaBot as well as an initial analysis of the durability, both of the display as well as of the actuator.

CCS Concepts: • **Human-centered computing** → **Human computer interaction (HCI)**; • **Computer systems organization** → **Robotics**.

Additional Key Words and Phrases: Human-robot interaction; soft robotics; display; electrochromic displays

ACM Reference Format:

Anna Dagmar Bille Milthers and Markus Löchtefeld. 2021. ChromaBot - Prototyping Soft Robotic Actuators with Integrated Electrochromic Displays. In *20th International Conference on Mobile and Ubiquitous Multimedia (MUM 2021)*, December 5–8, 2021, Leuven, Belgium. ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/3490632.3497831>

1 INTRODUCTION

Soft robotics have in the last years emerged as a new class of robotic actuators. Their defining characteristic is that they are built from highly compliant materials with Young moduli that are close to soft biological materials [19]. Besides other [14], the most prominent application for soft robots is to be used as a robotic gripper, as their softness allows to grab irregular shaped and fragile objects¹. Given their softness they are also particularly well suited for human

¹<https://www.festo.com/group/en/cms/12745.htm>

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

© 2021 Copyright held by the owner/author(s).

Manuscript submitted to ACM




Fig. 2. Left: Composition of the ChromaBot layers using a co-planar stack with PET-ITO as top- and normal PET as bottom layer all encapsulated by silicone. Right: The evaluation prototype with a simple pattern that is split in two states and each activated.

robot collaboration as the danger of injuring the human collaborator is rather small [3, 14, 15]. However, they have limited capabilities to communicate, their intention and future actions to a human collaborator. If the soft robot fails in completing its task and cannot self-correct its behavior, a human may be needed to assist it and the current state of soft robotics only allow for the usage of movement [13, 15] or external augmentations such as sound [1] to communicate such issues. This multi-modal interplay of different interaction partners with asymmetric communication capabilities is a general issue in HRI [2, 5], however, with rigid robots, it is easy to attach e.g., displays that can assist in communication. Adding rigid components to a soft robotic actuator would decrease its main defining characteristic. While flexible OLED or E-ink displays are becoming more common they still require "hard" electronics for the display drivers and their high-price point make them less suited for prototyping. The field of printed electronics has recently developed to a point at which thin and flexible displays can be printed at comparable low costs [7, 17]. In this paper we present ChromaBot, a method towards prototyping soft robotic actuators with integrated printed electrochromic (EC) displays. Through an experimental prototyping approach we developed a construction method, that degrades the longevity of the soft robotic actuator in an acceptable manner while at the same time allows for a more expressive soft robot.

2 METHOD & EVALUATION

We followed an experimental approach to develop a method to integrate EC displays into a soft robotic actuator. The reason for choosing EC displays is that they are easy to produce and have a proven track record in interactive artefacts [9–11] and can be integrated easily with other materials such as paper [12, 16] or be used as part of a wearable [4, 8]. We followed previous work and used the PneuNet design for our actuators [6]. PneuNet actuators are made of two layers that are merged, the extensible layer and the inextensible layer. The extensible layer - usually cast from a highly compliant silicon - contains several air chambers that, once pressurized, expands and is thereby bending the actuator given that the inextensible layer does not expand. For ChromaBot we decided to use an EC display cast in silicone as the extensible layer. Given that most current display technologies are not stretchable, it is the most logical choice to integrate the display in the inextensible layer which is supposed to be less compliant. For our approach we decided to produce the EC display in a co-planar stack following the method described in [7] using flexible PET-ITO. The reason to chose a co-planar stack over a vertical stack is, that the latter is comprised out of two layers of PET-ITO facing each other that potentially could under stress and pressure touch each other and short-circuit. With a co-planar stack there is no risk for this. We tested over 25 different combinations and building styles before we arrived at the final combination. A cross-section of the final construction of ChromaBot can be seen in Figure 2 (left). Building the inextensible layer consist of the following steps: Firstly one builds a co-planar EC display consisting of a layer of

PET-ITO, EC-ink, electrolyte and normal PET. Then a flat thin layer of silicone is produced and cured. After that the EC display is placed on it and more silicone is cast around it and on the top of it which should also be cured. The PET-ITO layer of the EC display should face the outside of the actuator leading to a clearer visible display. The PET-ITO should extend further out of the extensible layer so that the connection leads to digitally control the display can be connected (compare Figure 1 right). Lastly, another layer of silicone is placed on this to fuse the extensible layer (cast priority from silicone in a suited mold) to the inextensible layer.

We evaluated this method by constructing 10 actuators following the above described steps as well as 5 actuators without a display where the inextensible layer was build with textile (made 100% from cotton). The silicone that was used was uncolored ecoFlex 00-30 from Smooth-On. The final design of the actuator can be seen in Figure 2 (right). We used a more complex actuator with a rounded end that was 14cm long. The used design for the display was a simple pattern that was meant to enhance the aesthetics of the actuator with no specific application in mind. The switching time of the displays (meaning an activation until no visual optical change was perceivable) after they were cast in silicone was between 9-10 seconds (avg 9,67s). To test the durability of the actuator we fixated one end of an actuator to a table using adhesive tape and exposed the actuators to continuous complete inflation and deflation cycles. After every 200 cycles we tested the switching time of the display. We measured the average time it took until no visual optical change was perceivable. We cycled the actuators through inflation and deflation cycles until they would break (meaning that they would not inflate anymore). This occurs usually due to either the extensible or inextensible layer disintegrating or the two layers separating from each other. The actuators were pneumatically inflated by a Mitsumi air pump, to which also a valve was attached to release air from the chambers to deflate the robot. The pump and valve are controlled by an Arduino Uno with a motor shield. On average the ChromaBot actuators all lasted for over 1400 cycles of inflation and deflation (avg. 1591) before they would disintegrate, in comparison the normal actuators all lasted over 1700 cycles (avg. 1923) before breaking. The mostly observed reason for this decreased lifetime is that the silicone separates from the display making the displays move in its cavity in the inextensible layer and ultimately breaking it. In terms of display switching time no differences were found during the tests compared to the starting point.

3 DISCUSSION & CONCLUSION

Overall the ChromaBot actuators performed very well and why they did pose a decrease in durability compared to the normal actuators, it is still acceptable for prototyping purposes. While EC displays come with some disadvantage e.g. not being light emissive, given that the characteristics of electroluminescent (EL) displays in terms of thickness and flexibility are very similar to them and that they also can be produced using PET-ITO [17] it should be possible to replace the EC display with an EL display in the ChromaBot build. This however, would need further investigation, but from a purely technical perspective it should result in similar actuator performance. It also should be mentioned that the actuators used and thereby its bend radius were rather large. This means that the PET-ITO was exposed to less stress. With smaller actuators this might change. While these limitations are not negligible, the ability to integrate digitally controlled displays is an advancement over existing approaches. We believe that ChromaBot can have a significant impact in enhancing soft robots communication channels to be more multi-modal. Our example actuators purely where equipped with a display demonstrating a pattern that was meant to be aesthetically pleasing. Besides these aesthetic or playful elements we especially hope, ChromaBot will be used to add more affordances, explanations or instructions to soft robotic actuators. It can play an active role in facilitating human robot collaboration using soft robotic actuators in the future. Furthermore, we also believe that this approach has the potential be used for future research in shape-changing devices [18].

REFERENCES

- [1] Mads Bering Christiansen and Jonas Jørgensen. 2020. Augmenting Soft Robotics with Sound. In *Companion of the 2020 ACM/IEEE International Conference on Human-Robot Interaction* (Cambridge, United Kingdom) (*HRI '20*). Association for Computing Machinery, New York, NY, USA, 133–135. <https://doi.org/10.1145/3371382.3378328>
- [2] Elizabeth Cha, Yunkyoung Kim, Terrence Fong, and Maja J. Mataric. 2018. A Survey of Nonverbal Signaling Methods for Non-Humanoid Robots. *Foundations and Trends in Robotics* 6, 4 (2018), 211–323. <https://doi.org/10.1561/23000000057>
- [3] Anca D Dragan, Andrea L Thomaz, and Siddhartha S Srinivasa. 2013. Collaborative manipulation: new challenges for robotics and HRI. In *Human-Robot Interaction (HRI), 2013 8th ACM/IEEE International Conference on*. IEEE, 435–436.
- [4] Çağlar Genç, Ashley Colley, Markus Löchtefeld, and Jonna Häkkinä. 2020. Face Mask Design to Mitigate Facial Expression Occlusion. In *Proceedings of the 2020 International Symposium on Wearable Computers* (Virtual Event, Mexico) (*ISWC '20*). Association for Computing Machinery, New York, NY, USA, 40–44. <https://doi.org/10.1145/3410531.3414303>
- [5] Guy Hoffman and Wendy Ju. 2014. Designing Robots with Movement in Mind. *J. Hum.-Robot Interact.* 3, 1 (Feb. 2014), 91–122. <https://doi.org/10.5898/JHRI.3.1.Hoffman>
- [6] Filip Ilievski, Aaron D Mazzeo, Robert F Shepherd, Xin Chen, and George M Whitesides. 2011. Soft robotics for chemists. *Angewandte Chemie* 123, 8 (2011), 1930–1935.
- [7] Walther Jensen, Ashley Colley, Jonna Häkkinä, Carlos Pinheiro, and Markus Löchtefeld. 2019. TransPrint: A Method for Fabricating Flexible Transparent Free-Form Displays. *Advances in Human-Computer Interaction 2019* (2019).
- [8] Walther Jensen, Ashley Colley, and Markus Löchtefeld. 2019. VitaBoot: Footwear with Dynamic Graphical Patterning. In *Proceedings of the 23rd International Symposium on Wearable Computers* (London, United Kingdom) (*ISWC '19*). Association for Computing Machinery, New York, NY, USA, 279–283. <https://doi.org/10.1145/3341163.3346937>
- [9] Walther Jensen, Brock Craft, Markus Löchtefeld, and Pernille Bjørn. 2022. Learning through interactive artifacts: Personal fabrication using electrochromic displays to remember Atari women programmers. *Entertainment Computing* 40 (2022), 100464. <https://doi.org/10.1016/j.entcom.2021.100464>
- [10] Walther Jensen, Hendrik Knoche, and Markus Löchtefeld. 2020. "Do You Think It is Going to Be the Cock?": Using Ambient Shadow Projection in Dialogic Reading. In *Proceedings of the 9TH ACM International Symposium on Pervasive Displays* (Manchester, United Kingdom) (*PerDis '20*). Association for Computing Machinery, New York, NY, USA, 97–103. <https://doi.org/10.1145/3393712.3395342>
- [11] Walther Jensen, Markus Löchtefeld, and Hendrik Knoche. 2019. ShadowLamp: An Ambient Display with Controllable Shadow Projection Using Electrochromic Materials. In *Extended Abstracts of the 2019 CHI Conference on Human Factors in Computing Systems* (Glasgow, Scotland Uk) (*CHI EA '19*). Association for Computing Machinery, New York, NY, USA, 1–6. <https://doi.org/10.1145/3290607.3313011>
- [12] Walther Jensen, Thomas Streubel Kristensen, Christoffer Sand Kirk, Hassan Abdul Hameed, Daniel Bergmann Villadsen, and Markus Löchtefeld. 2020. Hybrid Settlers - Integrating Dynamic Tiles into a Physical Board Game Using Electrochromic Displays. In *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems* (Honolulu, HI, USA) (*CHI EA '20*). Association for Computing Machinery, New York, NY, USA, 1–7. <https://doi.org/10.1145/3334480.3382857>
- [13] Jonas Jørgensen. 2018. Interaction with Soft Robotic Tentacles. In *Companion of the 2018 ACM/IEEE International Conference on Human-Robot Interaction* (Chicago, IL, USA) (*HRI '18*). ACM, New York, NY, USA, 38–38. <https://doi.org/10.1145/3173386.3177838>
- [14] Cecilia Laschi, Jonathan Rossiter, Fumiya Iida, Matteo Cianchetti, and Laura Margheri. 2016. Soft Robotics: Trends, Applications and Challenges. *Livorno, Italy* (2016).
- [15] Anna Dagmar Bille Milthers, Anne Bjerre Hammer, Jonathan Jung Johansen, Lasse Goul Jensen, Elizabeth Ann Jochum, and Markus Löchtefeld. 2019. The Helpless Soft Robot - Stimulating Human Collaboration through Robotic Movement. In *Extended Abstracts of the 2019 CHI Conference on Human Factors in Computing Systems* (Glasgow, Scotland Uk) (*CHI EA '19*). Association for Computing Machinery, New York, NY, USA, 1–6. <https://doi.org/10.1145/3290607.3312807>
- [16] Heiko Müller, Ashley Colley, Jonna Häkkinä, Walther Jensen, and Markus Löchtefeld. 2019. Using Electrochromic Displays to Display Ambient Information and Notifications. In *Adjunct Proceedings of the 2019 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2019 ACM International Symposium on Wearable Computers* (London, United Kingdom) (*UbiComp/ISWC '19 Adjunct*). Association for Computing Machinery, New York, NY, USA, 1075–1078. <https://doi.org/10.1145/3341162.3344844>
- [17] Simon Olberding, Michael Wessely, and Jürgen Steimle. 2014. PrintScreen: Fabricating Highly Customizable Thin-Film Touch-Displays. In *Proceedings of the 27th Annual ACM Symposium on User Interface Software and Technology* (Honolulu, Hawaii, USA) (*UIST '14*). Association for Computing Machinery, New York, NY, USA, 281–290. <https://doi.org/10.1145/2642918.2647413>
- [18] Anne Roudaut, Abhijit Karnik, Markus Löchtefeld, and Sriram Subramanian. 2013. Morphees: Toward High "Shape Resolution" in Self-actuated Flexible Mobile Devices. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems* (Paris, France) (*CHI '13*). ACM, New York, NY, USA, 593–602. <https://doi.org/10.1145/2470654.2470738>
- [19] Daniela Rus and Michael T Tolley. 2015. Design, fabrication and control of soft robots. *Nature* 521, 7553 (2015), 467.