

## Quantification and Management of fine sediments in Streams

Fuglsang, Emil Dietz; Pedersen, Morten Lauge

*Publication date:*  
2011

*Document Version*  
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*  
Fuglsang, E. D., & Pedersen, M. L. (2011). *Quantification and Management of fine sediments in Streams*. Poster presented at The International Conference : restoration of streams with special emphasis on the houting and the houting project, Tønder, Denmark.

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

### Take down policy

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.

## Quantification and management of fine sediments in streams

*Emil Dietz Fuqlsang - Morten Lauge Pedersen*

*Water and Environment, Aalborg University, Sohngaardsholmsvej 57, DK-9000 Aalborg, DK*

To improve drainage of agricultural areas channelization of streams has been carried out during the past centuries. As a result of the channelization of many Danish streams, the streams are left void of natural stones and gravel and an excessive sediment transport has been started.

Many projects have been carried out focusing on reintroducing gravel in small and large streams. The positive effects of reintroducing spawning gravel has some places been minimized due to the amount of fine sediments present in regulated streams. The negative consequences of high levels of infiltrated fines have been shown in numerous studies. Infiltrated fines block the exchange of oxygen rich water to the eggs of salmonids and thus kill the eggs [1].

In order to control and lower the sediment transport in streams sediment traps are widely used. The traps are constructed upstream the gravel area by excavating a segment of the stream in order to make the stream wider and deeper and there by store the sediment. These traps are to be emptied at appropriate time intervals. Design of sediment traps has traditionally been carried out following some general guidelines [2].

In this study, the effect of a sediment trap on the fine sediment deposition rates in reintroduced gravel in a small stream is investigated.

Along with the measurement of total sediments the grain sizes of the fines are measured. The infiltration rate is measured using infiltration baskets. These baskets were made of metal net with a mesh size of 6mm. They had a height of 250mm and a diameter of 240mm. Initially the baskets were filled with cleaned gravel and buried at a depth so the top of the basket raised the level of the gravel around the basket.

At fixed intervals the buried baskets were carefully taken up and the infiltrated fines were separated from the gravel and quantified. The baskets were then reburied again. Along with the basket measurements the flow and temperature of the water were measured.

[1] Sear, D.A., Frostick, L.B., Rollinson, G. and Lisle, T.E. (2008): The Significance and Mechanics of Fine-Sediment Infiltration and Accumulation in Gravel Spawning Beds. American Fisheries Society Symposium 65: 149-173 (2008)

[2] Bedre vandløb – en praktisk håndbog, Vejle Amt og Sønderjyllands Amt, ISBN 87-7750-530-1(2000)

