



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Enhanced methane productivity from lignocellulosic biomasses using aqueous ammonia soaking pretreatment

Jurado, Esperanza; Skiadas, Ioannis; Gavala, Hariklia N.

Published in:

Abstract in the proceedings of the 4th International Conference on Engineering for Waste and Biomass Valorisation 4th International Conference on Engineering for Waste and Biomass Valorisation (WasteEng12), Porto (Portugal), September 10-13

Publication date:

2012

Document Version

Early version, also known as pre-print

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Jurado, E., Skiadas, I., & Gavala, H. N. (2012). Enhanced methane productivity from lignocellulosic biomasses using aqueous ammonia soaking pretreatment. In Abstract in the proceedings of the 4th International Conference on Engineering for Waste and Biomass Valorisation 4th International Conference on Engineering for Waste and Biomass Valorisation (WasteEng12), Porto (Portugal), September 10-13 (Vol. 4, pp. 1223). WasteEng Conference Series, Mines d'Albi, France.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

ENHANCED METHANE PRODUCTIVITY FROM LIGNOCELLULOSIC BIOMASSES USING AQUEOUS AMMONIA SOAKING PRETREATMENT

E. JURADO¹, I.V. SKIADAS¹ and H.N. GAVALA^{1,*}

¹ Aalborg University Copenhagen (AAU-Cph), Department of Biotechnology, Chemistry and Environmental Engineering, Lautrupvang 15, DK 2750 Ballerup, Denmark.

*Corresponding author: e-mail: hng@bio.aau.dk, hari_gavala@yahoo.com, tel: +4599402586, fax: +45 99402594.

Keywords: anaerobic digestion, aqueous ammonia soaking, miscanthus, methane potential, wheat straw, willow.

Extended Abstract

The continuously increasing demand for renewable energy sources, such as methane, renders anaerobic digestion to one of the most promising technologies for renewable energy production. In fact, anaerobic digestion for methane production has become a major part of the rapidly growing renewable energy sector. Biogas is part of a rapidly growing renewable energy sector, which expands at a rate of 20-30 % globally [1]. However, the increasing demand for methane production cannot be satisfied by the use of anaerobic digestion only from waste/wastewater treatment. Energy crops as well as agricultural residues, such as wheat straw, can be considered as one of the best options for increasing the methane production through biomass digestion. The production of perennial crops like miscanthus, sweetgrass, and willow consumes far less resources (energy for cultivation, herbicides and fertilizers) compared to annual crops [2]. However, the efficiency of methane production from perennial crops and lignocellulosic residues is limited by the low biodegradability of the lignocellulose. The destruction of the lignocellulosic structure will release the sugars contained in the biomass and therefore can dramatically increase the production of methane.

In the present study, aqueous ammonia soaking (AAS) and subsequent ammonia removal has been successfully applied as a method to disrupt lignocellulosic structure and increase methane potential and biogas productivity using wheat straw, miscanthus and willow as feedstock. AAS presents certain advantages as a pretreatment method. Ammonia is safe to handle, non-polluting and non-corrosive and can be easily recovered due to its high volatility[3].

In all three cases, an increment in methane potential has been observed. Methane production after 50 days exhibited an increase of 37%, 23% and 96% for wheat straw, miscanthus and willow, respectively. Moreover, sugar analyses showed that AAS resulted in no solubilization of sugars.

REFERENCES

- [1] UNEP, 2008 Global Trends in Sustainable Energy Investment 2008 Report. (http://www.unglobalcompact.org/docs/issues_doc/Environment/climate/Global_Trends_2008.pdf).
- [2] U.S DOE., 2006 Breaking the Biological Barriers to Cellulosic Ethanol: A Joint Research Agenda. DOE/SC-0095, UNEP. 2006, www.doe.genomestolife.org/biofuels/.
- [3] Kim, M.; Aita, G. And Day, D. F, 2010 Compositional Changes in Sugarcane Bagasse on Low Temperature, Long-Term Diluted Ammonia Treatment. *Appl .Biochem. Biotechnol*, 2010, vol. 161, no. 1-8. pp. 34-40.