



**AALBORG UNIVERSITY**  
DENMARK

**Aalborg Universitet**

## **Innovative Design of Vertical Axis Wind Turbine**

*a poster presented at DAMAS 2013 conference*

Chougule, Prasad

*Published in:*

10th International Conference on Damage Assessment of Structures (DAMAS 2013), July 8-10, 2013, Dublin, Ireland

*Publication date:*

2013

*Document Version*

Early version, also known as pre-print

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*

Chougule, P. (2013). Innovative Design of Vertical Axis Wind Turbine: a poster presented at DAMAS 2013 conference. In *10th International Conference on Damage Assessment of Structures (DAMAS 2013), July 8-10, 2013, Dublin, Ireland*

### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

### **Take down policy**

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.

# Innovative Design of Vertical Axis Wind Turbine

Prasad D. Chougule

Department of Civil Engineering, Aalborg University, Denmark.

pdc@civil.aau.dk

## Introduction

The wind turbines can be classified as: i) Horizontal axis wind turbines (HAWT), and ii) Vertical axis wind turbines (VAWT). The HAWT is fully developed and the size is growing higher. Whereas, the VAWT is not developed because of the less efficiency and vibration issues of big structure. However, it is well known that the VAWT is advantages over a HAWT in terms of a cost and the simplicity (Paraschivoiu 2002). In this PhD project a simple blade design is incorporated by using the two-element airfoil technology for a three straight-bladed VAWT. The design considerations of a two airfoil are given, and its aerodynamic characteristics are obtained by an experimental method. A new design is called  $D^2A - VAWT$  and a test ring is made to validate the numerical results. A double multiple stream tube method (DMSTM) and blade element method (BEM) are used to determine the numerical performance of a proposed  $D^2A - VAWT$ .

## Objectives

The objectives of this PhD project are :

1. Improvement of mechanical efficiency and a self-start ability of a three straight-bladed VAWT.
2. Design a test ring of a proposed  $D^2A - VAWT$  for validation of the numerical results.
3. Implementation of an active blade pitch control mechanism for a proposed  $D^2A - VAWT$ .

## Methods

An experimental and a numerical method is used to design and develop an innovative three straight-bladed VAWT. A two-element airfoil blade design is incorporated in a proposed  $D^2A - VAWT$  and a layout of two-element airfoil is shown in Figure 1.




Figure 1.: S1210 single airfoil (SA) and design of S1210 two-element airfoil (DA)

The various methods used to achieve the objectives of PhD project are:

1. Experimental:
  - a. A wind tunnel is used to obtain the aerodynamic characteristics of the designed two-element airfoil to validate numerical results.
  - b. A test ring is made to obtain the performance of a proposed  $D^2A - VAWT$ .
2. Numerical: A Computational Fluid Dynamic (CFD) tool is used for simulation of a 2-dimensional flow over a designed two-element airfoil.
3. A DMSTM and a BEM is used to determine the performance of a proposed  $D^2A - VAWT$ .

## Results

CFD simulation results for a single (SA) and a two-element airfoil are given in Figure 2.




Figure 2.: Lift coefficient of a SA and a DA S1210 airfoil.

Performance of a reference VAWT (Huskey et al. 2009) and a proposed  $D^2A - VAWT$  is given in Figure 3




Figure 3. a) Power coefficient and b) Total power output.

- : Measurements of a reference wind turbine .
- : Numerical results of a reference wind turbine .
- : Numerical results of a proposed  $D^2A - VAWT$ .

## Conclusion

Two-element airfoil blade design is incorporated in a proposed  $D^2A - VAWT$  to improve the power efficiency and self start ability of a reference VAWT. In this work only 2D aerodynamic characteristics of a single and a two-element airfoil are given which are validated by wind tunnel experiments. It is observed that the mechanical power efficiency of a three straight-bladed VAWT is improved to 40%. An experimental test ring is made and subsequently the testing will be carried out to validate the numerical results.

## References

- Paraschivoiu I., Wind Turbine Design: with Emphasis on Darrieus Concepts. Polytechnic International Press, ISBN: 978-2-553-00931-0 (2002).
- Huskey, A. B. and Jager D., Wind turbine generator system power performance test report for the Mariah Windspire 1-kw wind turbine, National Renewable Energy Laboratory, Technical report NREL/TP-500-46192, December (2009).

The SYSWIND project (project no. 238325) funded by the Marie Curie Actions is acknowledged for the financial support under the grant Seventh Framework Programme for Research and Technological Development of the EU.

DAMAS 2013 10<sup>th</sup> International Conference on Damage Assessment of Structures

8<sup>th</sup> July - 10<sup>th</sup> July, Ireland, Dublin.

