



**AALBORG UNIVERSITY**  
DENMARK

**Aalborg Universitet**

## **Model Estimation of HTPeM Mea Parameters from EIS and IV Curves**

Vang, Jakob Rabjerg; Zhou, Fan

*Publication date:*  
2015

*Document Version*  
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*

Vang, J. R., & Zhou, F. (2015). *Model Estimation of HTPeM Mea Parameters from EIS and IV Curves*. Abstract from Electrochemical science and technology conference 2015, København, Denmark.

### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

### **Take down policy**

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.



## MODEL ESTIMATION OF HTPEM MEA PARAMETERS FROM EIS AND IV CURVES

Jakob Rabjerg VANG<sup>1</sup>, Fan ZHOU<sup>1</sup>

<sup>1</sup>Aalborg University, Denmark, jrv@et.aau.dk

Impedance spectra can be a valuable supplement to polarisation curves when characterising a fuel cell membrane-electrode-assembly (MEA). This work presents a finite-volume based high temperature PEM (HTPEM) fuel cell model for estimating MEA parameters from impedance spectra and polarisation curves by simultaneous fitting. One of the challenges in the model development concerns the modelling of the catalyst layer. This work explores the impact of some of the different assumptions on the fit and the estimated MEA parameters.

One of the most important choices is that of catalyst layer (CL) model. Two different CL models have been implemented. One assumes that the Pt catalyst sits on the surface of the carbon substrate and is covered by a thin film of phosphoric acid (PA). The other approach assumes that the catalyst particles are collected in agglomerates flooded with PA. The fits are compared in the figures. Note that the agreement with the data is similar for the two catalyst models. The parameter values estimated generally agree well with available data from literature and are mostly similar regardless of the CL model. Only the CL PA content, the CL thickness, and the surface area of the CL pores vary significantly between CL models. The discrepancies relate to differences in reactant transport characteristics of the CL models. The PA content also deviates from literature values. This is assumed to result from PA migration during operation.

The model is suitable for the analysis of data from degradation tests.

